




iPlay Wall mount plastic loudspeakers


INSTALLATION MANUAL

- These speakers are manufactured in order to resist from variety of weather conditions, but they are not water-proof, so if you decide to place these loudspeakers in outdoor, please, be sure that there will be a protection from direct precipitation. The underside of most eaves and overhangs provide the best protection in outdoor using.
- Like all speakers, sound is the best when loudspeaker is placed not far than seven feet from the ear level of listeners. If the loudspeakers are further than seven feet, it must be directed in to the center of the room. Do not place them closer than two feet of television or computer screen, because these speakers are not magnetic shielded.
- If your applications require mounting speaker on the wall, please follow these directions:
 1. Mount the bracket on the wall
 2. Attach the loudspeaker to the bracket and fix it with the large plastic knobs.
 3. Connect the wires from amplifier and set the needful loudspeakers power.
- Never mount a speaker on the wall which is made of unreinforced drywall or plasterboard. If you are unsure, please consult with a professional contractor.
- The binding post terminals on the speakers will accommodate up to 12 gauge wire. When connecting the speakers, it is very important to observe the correct polarity. That means that wire attached to the positive (red) component on the amplifier must be attached to the positive (red) terminal on the loudspeaker. The negative (-) wire from the amplifier must be connected to the negative speaker's terminal.
- The 100V transformer mounted in the loudspeakers offers the ability to connect a various number of loudspeakers in parallel. In that case you must use a power amplifier which is adapted for 100V audio line. When loudspeaker is connected in to 100V line, you can select loudspeaker's power by the external power's selector which is placed on the rear loudspeakers side. If loudspeaker is using with low impedance amplifier's power, selector must be set on 8Ω position.


Mounting instruction



1



2



3

1. Mount U-bracket on the wall and fix it by screws.
2. Place loudspeaker in to the bracket and fix.
3. Connect the wires and set needful loudspeakers power.