

# GXR-D15A

## Key features

- Class D Powered
- Integrated Digital Processing
- Internal temperature control
- Electronic protection
- Online monitoring available

## Applications

- Live events
- Clubs
- Houses of worship
- Theatres
- Fixed installations
- Touring



## General description & specs

High Output, self powered (class D switch mode power supply with PFC), omni-directional subwoofer cabinet.

Consists of 2 x 15" (4" voice coil) neodymium transducer. DSP controlled with 2400W amplification, 134 dB SPL

Components	LF: 2 x 15" (4" voice coil), neodymium magnetic assembly	Processing	96 KHz / 56 bit double precision DSP
		Control	User control interface with LCD
Frequency Range	30 Hz – 140 Hz (-10dB) processed	Control Connections	USB (DSP programming)
Frequency Response	35 Hz – 125 Hz ( $\pm$ 3dB) processed	AC Power	90 – 264V. 50/60 Hz with PFC
Max. SPL	134 dB	AC Connections	16A Neutrik powerCon TRUE1 with looping output
Coverage	Omnidirectional	Finish	High resistant water-based black paint
Power	2400 W Class D with switching power supply & PFC	Material	18mm Premium birch plywood
LF Amplifier	2 x 1200 W	Dimensions (H x W x D)	505 x 790 x 690 mm
		Weight	48 Kg (105 lbs)