

ARK105MP



5"



1"



140°x140°



WALL MOUNT



DEDICATED PRESET



ARK105MP

2-way passive loudspeaker, 120W AES, 114dB SPL

- Low frequency: 5 " woofer/0.75" v.c.
- High frequency: 1 " driver / 1.5" v.c.
- Frequency response: 75-18000 Hz (± 3 dB)
- ARK105MP full range speakers are suitable for small installations or can be used as satellites in combination with the passive or active sub.
- The DAD logo on the grille can be rotated rapidly for the both vertically and horizontally installation.
- Birch plywood enclosure.

ARK105MP TECHNICAL DATA

LOUDSPEAKERS

- System type: passive 2 way

COMPONENTS

- Low frequency: 5" woofer/1.5" v.c.
- High frequency: 1" driver/1" v.c.

FEATURES

- AES/program power: 120/240W
 - SPL max: 114dB @1m (free field)
- #### ACOUSTICAL SPECIFICATIONS
- Sensitivity: 89dB @1W/1m (free field)
 - Impedance: 16 Ohm
 - SPL cont/peak: 108/114dB @1m (free field)
 - Frequency response: 75-18000Hz (± 3 dB)
 - Coverage angle HxV: 140x140°
 - Cross over frequency: 2300Hz
 - Protection: H.F. signal compression
 - Suggest HPF range: 140/180Hz
 - Recommended amplifier up to: 240W /16Ohm

INPUT/OUTPUT CONNECTORS

- Input signal: 4pole - terminal clamp IN/OUT

CABINET CONSTRUCTION

- Cabinet material: 12mm plywood
- Sospension system: wall brackets (included)
- Angle: 7.5° trapezoidal taper

PHYSICAL

- Dimensions (WxHxD): 186x310x208mm
- Weight: 5.9kg

Versions:

ARK105MPBK (Black finish) **ARK105MPWH** (White finish)