# ARK106MP















### ARK106MP

2-way passive loudspeaker, 120W AES, 116dB SPL

- Low frequency: 6 "woofer/0.75" v.c.
- High frequency: 1 " driver / 1.5" v.c.
- Frequency response:75-18000 Hz (±3dB)
- ARK106 full range speakers are suitable for small installations or can be used as satellites in combination with the passive or active sub.
- The DAD logo on the grille can be rotated rapidly for the both vertically and horizontally installation.
- Birch plywood enclosure.

## ARK106MP TECHNICAL DATA

#### LOUDSPEAKERS

- System type: passive 2 way COMPONENTS
- Low frequency: 6" woofer/1.5"v.c.
- High frequency: 1" driver/1"v.c. FEATURES
- AES/program power: 120/240W
- SPL max: 116dB @1m (free field)

#### **ACOUSTICAL SPECIFICATIONS**

- Sensitivity: 92dB @1W/1m (free field)
- Impedence: 16 Ohm
- SPL cont/peak: 110/116dB @1m (free field)
- Frequency response: 75-18000Hz (±3dB)
- Coverage angle HxV: 140x140°
- Cross over frequency: 2500Hz
- Protection: H.F. signal compression
- Suggest HPF range: 120/160Hz
- Recommended amplifier up to: 240W /16Ohm

## INPUT/OUTPUT CONNECTORS

• Input signal: 4pole - terminal clamp IN/OUT CABINET CONSTRUCTION

# Cabinet material: 12mm plywood

- Sospension system: wall brakets (included)
- Sospension system, wan brakets (inclu

# • Angle: 7.5° trapezoidal taper

- PHYSICAL
- Dimensions (WxHxD): 201x340x233mm
- Weight: 6.5kg

## **Versions:**

**ARK106MPBK** (Black finish) **ARK106MPWH** (White finish)