



ARK205MP

Active sub woofer 600W with 2x300W/4 Ohm stereo output.

- Low frequency: 2x8 " woofer/2" v.c.
- Frequency response: 40/200 Hz (±3dB)
- Adjustable Crossover: LPF: 80/120 Hz - HPF 22, 80, 125 Hz
- Can be used with full range speakers in the ARK series.
- Possible combinations ARK1200SA + 2 x ARK105 / 106 / 205 / 206, up to 4 for each channel.
- Birch plywood enclosure.

Versions:

ARK1200SABK (Black finish)

ARK1200SAWH (White finish)

ARK1200SA



2x8"



DIGITAL AMP



ANALOG PROC



140°x140°



WALL MOUNT



LPF CONTROL



OUT HPF

ARK1200SA TECHNICAL DATA

LOUDSPEAKERS

- System type: active subwoofer with amplified stereo out

COMPONENTS

- Low frequency: 2x8" woofer/2" v.c.

FEATURES

- Amplified subwoofer: Built-in amp LF 600 + MF/HF 2x300W 4Ohm
- Adjustable crossover: LPF: 80/165 Hz - HPF 22, 80, 125 Hz

ACOUSTICAL SPECIFICATIONS

- SPL cont/peak: 120/126dBdB @1m (free field)
- Frequency response: 40/200Hz (±3dB)
- Coverage angle HxV: omnidirectional

ELECTRONICS

- Amplifier: Digital
- Power: 600+2x300W /4Ohm
- Input sensitivity: 4 dBu (1,228Vrms) adjustable
- Protection: limiter temp.
- User controls: mic, line, master, eq LF-HF
- Operating voltage/frequency: 220 V~240 V/50 Hz

INPUT/OUTPUT CONNECTORS

- Input signal: XLR IN/OUT, jack 6.35 mm, pin RCA unbal.
- Output signal: 2 x 4 pole
- Power connection: powerCON IN/OUT

CABINET CONSTRUCTION

- Cabinet material: 15mm plywood
- Suspension system: wall brackets (included)

PHYSICAL

- Dimensions (WxHxD): 500x246x325mm
- Weight: 14.5kg