# ARK205MP

















#### LOUDSPEAKERS

System type: passive 2 way

### **COMPONENTS**

- Low frequency: 2x5" woofer/1.5"v.c. • High frequency: 1" driver/1"v.c.
- FEATURES
- AES/program power: 240/480W
- SPL max: 119dB @1m (free field)

#### **ACOUSTICAL SPECIFICATIONS**

- Sensitivity: 92dB @1W/1m (free field)
- Impedence: 16 Ohm
- SPL cont/peak: 113/119dB @1m (free field)
- Frequency response: 75-18000Hz (±3dB)
- Coverage angle HxV: 140x140°
- Cross over frequency: 2200Hz
- Protection: H.F. signal compression
- Suggest HPF range: 140/180Hz
- Recommended amplifier up to: 480W /16Ohm

### INPUT/OUTPUT CONNECTORS

Input signal: 4pole - terminal clamp IN/OUT

## CABINET CONSTRUCTION

- Cabinet material: 12mm plywood
- Sospension system: wall brakets (included)
- Angle: 7.5° trapezoidal taper

### PHYSICAL

- Dimensions (WxHxD): 186x438x208mm
- Weight: 8.6kg

# ARK205MP

2-way passive loudspeaker, 240W AES, 119dB SPL

- Low frequency: 2x5 "woofer/0.75" v.c.
- High frequency: 1 " driver / 1.5" v.c.
- Frequency response:75-18000 Hz (±3dB)
- ARK205MP full range speakers are suitable for small installations or can be used as satellites in combination with the passive or active sub.
- The DAD logo on the grille can be rotated rapidly for the both vertically and horizontally installation.
- Birch plywood enclosure.

### Versions:

ARK205MPBK (Black finish) ARK205MPWH (White finish)