

ARK206MP



ARK206MP

2-way passive loudspeaker, 240W AES, 122dB SPL

- Low frequency: 2x6" woofer/0.75" v.c.
- High frequency: 1" driver / 1.5" v.c.
- Frequency response: 65-18000 Hz (±3dB)
- ARK206MP full range speakers are suitable for small installations or can be used as satellites in combination with the passive or active sub.
- The DAD logo on the grille can be rotated rapidly for the both vertically and horizontally installation.
- Birch plywood enclosure.

Versions:

ARK206MPBK (Black finish) **ARK206MPWH** (White finish)



2x6"



1"



140°x140°



WALL MOUNT



DEDICATED PRESET

ARK206MP TECHNICAL DATA

LOUDSPEAKERS

- System type: passive 2 way

COMPONENTS

- Low frequency: 2x6" woofer/1.5" v.c.
- High frequency: 1" driver/1" v.c.

FEATURES

- AES/program power: 240/480W
- SPL max: 122dB @1m (free field)

ACOUSTICAL SPECIFICATIONS

- Sensitivity: 95dB @1W/1m (free field)
- Impedance: 16 Ohm
- SPL cont/peak: 116/122dB @1m (free field)
- Frequency response: 65-18000Hz (±3dB)
- Coverage angle HxV: 140x140°
- Cross over frequency: 2100Hz
- Protection: H.F. signal compression
- Suggest HPF range: 120/160Hz
- Recommended amplifier up to: 480W /16Ohm

INPUT/OUTPUT CONNECTORS

- Input signal: 4pole - terminal clamp IN/OUT

CABINET CONSTRUCTION

- Cabinet material: 12mm plywood
- Suspension system: wall brackets (included)
- Angle: 7.5° trapezoidal taper

PHYSICAL

- Dimensions (WxHxD): 202x498x233mm
- Weight: 9.5kg