

ARK403MP



4x3"



115°x20°



WALL MOUNT



ARK403MP

Wall mounted column loudspeaker, 100W AES, 114dB SPL

- Mid frequency: 4x3" midrange / 0.75" v.c.
- Frequency response: 135-17000 Hz (± 3 dB)
- Coverage angle HxV: 115x20°
- The modules with 4 transducers of 3" represent the solution to sound in deep environments particularly difficult, where quality and intelligibility are required.
- Column modules with an off-axis transducer for wide horizontal dispersion.
- Aluminium frame for a very robust yet lightweight design that fits in with any environment.

Versions:

ARK403MPBK (Black finish)

ARK403MWH (White finish)

ARK403MP TECHNICAL DATA

LOUDSPEAKERS

- System type: column loudspeaker

COMPONENTS

- Mid frequency: 4x3" midrange / 0.75" v.c.

FEATURES

- AES/program power: 100/200W
- SPL max: 114dB @1m (free field)

ACOUSTICAL SPECIFICATIONS

- Sensitivity: 92dB @1W/1m (free field)
- Impedence: 8 Ohm
- SPL cont/peak: 108/114dB @1m (free field)
- Frequency response: 135-17000Hz (± 3 dB)
- Coverage angle HxV: 115x20°
- Suggest HPF range: 140/180Hz
- Recommended amplifier up to: 200W /8Ohm

INPUT/OUTPUT CONNECTORS


- Input signal: XLR IN/OUT, pin RCA unbal.

CABINET CONSTRUCTION

- Cabinet material: 3mm aluminum die cast
- Sospension system: wall brakets (included)

PHYSICAL

- Dimensions (WxHxD): 110x350x148mm
- Weight: 5.8kg



The brackets allow a rotation on the horizontal plane of 180° to step of 15° and a tilt on the vertical plane of 30° to 8° step.



Screw for the rotation on the horizontal plane.