



5.25" cone woofer with a 0.75" soft dome tweeter

---

**A versatile lineup for clear consistent sound**

**Specifications**

General specifications		
Speaker type		2-way, Bass-reflex
Frequency range (-10dB)		62Hz - 20kHz
Nominal coverage	H	120°
	V	120°
Components	LF	5.25" Cone
	HF	0.75" Soft dome
Power rating	NOISE	75W
	PGM	150W
Nominal impedance		8Ω
SPL	Sensitivity (1W; 1m on axis)	89dB SPL
	Peak (Calculated)	114dB SPL
I/O connectors		1x Euroblock (4P) (Input: + / -, Loop Thru: + / -)
Dimensions	W	176mm (6.9")
	H	280mm (11.0")
	D	163mm (6.4")
Net weight		3.6kg (7.9lbs)
Shape		Rectangular
Cabinet material		ABS
Finish		VXS5:Black / VXS5W:White
Accessories		Wall / Ceiling mount bracket, Terminal cover
Others		Packaged in pair
Crossover		3kHz
Transformer taps	100V	30W (330Ω), 15W (670Ω), 7.5W (1.3kΩ)
	70V	30W (170Ω), 15W (330Ω), 7.5W (670Ω), 3.8W (1.3kΩ)
Waterproof		IP35
Packaging		Packaged in pairs
Certificate		UL1480, NFPA70, CE, EAC, RoHS
EN54-24 compliance		-