

# LumiPix XB100

IP65, 100 cm (18 pixels) RGB+WW, pixel-controlled linear LED fixture

ORDER CODE: **LUMIPIXXB100**

The **Lumipix** XB is a family of IP65 rated, pixel-controlled linear LED fixtures.

The units are available in 100 cm (18 pixels) and 50 cm (9 pixels) - the 20W RGB + Warm White LEDs deliver a punchy beam of light with bright, vibrant colours and high CRI.

The beam angle of the **Lumipix** XB can easily be adjustable with holographic beam shaper filters or with the optical accessories.

These units were specifically made for live productions, and include control options like DMX/RDM, Ethernet and Wireless DMX (CRMX and W-DMX), sharing the same user settings and capabilities as the theatrical and broadcast luminaires.

## MAIN FEATURES

- IP65, pixel-controlled LED linear fixture, available in 18 pixels and 9 pixels
- High CRI (90+), advanced colour control and effects generator
- DMX/RDM control, Ethernet, and Wireless DMX (CRMX + W-DMX)

## TECHNICAL SPECIFICATION

### LIGHT SOURCE

- Source: 18x20 W RGB + Warm White LEDs (driven @ 430W)
- Luminous flux: 5'083 lm @full
- Luminous flux: TBD
- Lux: 10'932 lx @3 m
- Lux: 3'936 lx @5 m
- CRI: TBD
- R9: TBD
- TLCI: TBD
- TM30 Rf: TBD
- TM30 Rg: TBD
- Source life expectancy: > 50.000 h

### OPTICS

- Beam angle: 11 °
- Field angle: 19 °
- Lens type: different optics available
- Additional optics: magnetics filters available

### COLOUR SYSTEM

- Colour mixing: RGB + Warm White
- CCT: CCT control, + / - green correction, tungsten emulation
- White presets: 2.800 K - 10.000 K with 28 K resolution
- Colour wheel: virtual colour wheel with macros

### DYNAMIC EFFECTS

- Control Resolution: 16-bit dimmer, colours
- Pixel patterns: pre-programmed pixel macros and cinema lighting effects patterns
- Special features: linear crossfade channel from any white to any colour; virtual CTO on colours

### BODY

- Body: sturdy die-cast aluminium body
- Body colour: black

### CONTROL

- Protocols: DMX512, RDM, Art-Net, sACN, W-DMX
- Pixel control: 18 pixel2pixel control

- Wireless Control: included, Lumen Radio Timo Fx DMX/RDM compatible with both CRMX (Lumen Radio) and W-DMX (Wireless DMX)
- RDM: RDM for remote monitoring and settings
- Display: Graphic User Interface
- Firmware upgrade: yes, via USB - DMX interface (UPBOX1) not included
- Master/Slave: for synchronised operation of more units linked in a chain

### ELECTRONICS

- Dimmer: linear 0 ~ 100% electronic dimmer
- Dimmer curves: selectable dimming modes available
- Strobe / shutter: 1 - 30 Hz, electronic
- Display battery: self-charging battery backup
- Operating temperature: -20° ~ +45°
- LED Control: flicker free frequency with adjustable PWM
- Selectable PWM: 600 ~ 40.000 Hz

### ELECTRICAL

- Mains power supply: 100-240V - 50/60Hz
- Max power consumption: 250 W
- Output (at 230V): 8
- Power factor: >0,97

### PHYSICAL

- IP rating: 65 for temporary outdoor application, not for fixed installation
- Cooling: active, silent operation
- Suspension and fixing: hanging bracket for floor stand. Also can fit the fast quick lock OMEGA bracket
- Signal connection: Amphenol XLR 5p IN/OUT connectors
- Power connection: Seetronic powerCON TRUE IP65 IN/OUT
- Dimensions (WxHxD): 1.006x185x150 mm
- Weight: 7,5 kg


### CERTIFICATIONS / APPROVALS

- Certifications / Approvals: CE, UKCA, RCM, cTUVus, FCC


## ACCESSORIES & RELATED PRODUCTS

**PRESET FULL ON**

Beam angle 50%: Native



**TECHICAL DRAWINGS**



**CERTIFICATIONS / APPROVALS**



Conforms to UL STD. 1573  
 Certified to CSA STD: C22.2 NO. 166

Visit our website  
 for specifications and  
 tech documentations

