

# LD-1024DIN NET

B05032

## DESCRIPTION

1024 Channel DMX interface & Multizone controller with Ethernet port for Local Area Network (LAN, WLAN) that can be easily mounted on a DIN Rail

## FEATURES

- 1024 Channel DMX interface with ETHERNET port for Local Area Network (LAN, WLAN).
  - Can be used with the Wi-Light APP from a mobile device (Android + iOS) [Video 'Wi-Light 2 APP'](#)
  - 1024 output channels when used with a computer
  - Multizone 1024 output channels when used standalone without computer
- 30 minutes of Lighting, Audio and Video timeline synchronization with Pro DMX software
- Works with the Chromateq Led Player, Pro DMX, Pixxem, Studio DMX and Wi-Light 2 software (included).
- Functions and control in standalone mode:
  - Art-Net and sACN from SD card (including triggers)
  - Node to decode Art-Net and sACN to DMX (4 universes)
  - Automatic Real Time Clock triggering for different scenes (day, week, month, year)
  - External Triggering via 12 smart contacts
  - RS232 In/Out (16 characters for RS232 triggers, commands or orders)
  - UDP / Ethernet triggers and commands (from SDK)
  - Default start scene, scene priority, cross fade time
  - Total control via the Wi-Light 2 app (Android + iOS)
  - **Multiple Zone control: 10 different programs can run simultaneously**
  - Master/Slave mode for up to 64 interfaces connected together
  - An optional external infra-red receiver can be connected to the unit (LD-512Kit-IR = IR receiver + 2 remote controllers)
  - Micro SD card slot for memory extension
- Power supply: 5-24V, 0.2A input or 5V DC via USB-C

For more information about the software: [www.chromateq.com](http://www.chromateq.com)



[www.briteq-lighting.com](http://www.briteq-lighting.com) | <https://www.facebook.com/Briteq>

Beglec NV has the right to change products and specifications with and without notice. Major as well as minor changes can be involved. This leaflet can contain errors, therefore we advice to consult your local dealer to ensure that actual features and specifications match your requirements. Copyright © 2022 by BEGLEC NV. All rights reserved.



## TECHNICAL SPECIFICATIONS

<b>General : Dimensions (cm)</b>	11 x 10 x 6
<b>General : Weight (kg)</b>	0.5
<b>General : Energy Label</b>	No
<b>General : Color</b>	No
<b>General : Display</b>	No
<b>General : IP rating</b>	indoor
<b>Control : Protocol</b>	Art-Net, sACN, DMX
<b>Control : programmable</b>	Yes
<b>Control : upgradable software</b>	Yes
<b>Control : maximum DMX channels</b>	1024
<b>Connections : input</b>	screw terminal block (dmx), usb, RJ45
<b>Connections : output</b>	screw terminal block (dmx)
<b>Brand</b>	BRITEQ
<b>EANCode</b>	5420025650328

## YOUR DEALER



[www.briteq-lighting.com](http://www.briteq-lighting.com) | <https://www.facebook.com/Briteq>

Beglec NV has the right to change products and specifications with and without notice. Major as well as minor changes can be involved. This leaflet can contain errors, therefore we advice to consult your local dealer to ensure that actual features and specifications match your requirements. Copyright © 2022 by BEGLEC NV. All rights reserved.