



| Item No. | ZEWACW22 |
|--------------------------------------|---------------------|
| Housing Characteristics | |
| housing | swivel castor |
| mounting | plate |
| mounting dimension / hub / bolt hole | 105 x 80 mm / 52 mm |
| mounting / fork thickness | 3 mm / 2.50 mm |
| surface | zinc blue |

| | |
|------------------------------|---------------|
| Wheel Characteristics | |
| wheel center | polyamide |
| center colour | black |
| tread surface | elastic |
| tread colour | blue |
| bearing | ball bearing |
| threadguard | small plastic |
| threadguard colour | black |

| Technical Data | |
|--------------------|------------------|
| wheel - Ø | 125 mm |
| width of tread | 38 mm |
| width of hub | 50 mm |
| screw Size | 10 mm |
| plate hole centers | 80 / 77 x 60 mm |
| plate hole | 9.5 mm |
| offset | 39 mm |
| overall height | 155 mm |
| temparature range | - 20°C to + 80°C |
| hardness of tread | 65A |
| load capacity | 220 kg |

| Running Test | |
|---------------------|-------------------------|
| DIN | EN 12532 Standard |
| loading | 220 KG |
| number of obstacles | 2 (height of 6.25 mm) |
| testing | 500 times (250 circles) |
| obstacle running | 22 minutes |
| flat running | 96 minutes |
| total running | 108 minutes |
| running speed | 4 KM/H |

Result

No Damage!

ZEWACW22 has passed the test.

