SA-12

DESCRIPTION

Premium class 12" DSP-processed active speaker cabinet for a wide range of professional applications

FEATURES

- Professional active speaker cabinet for a wide range of different applications:
 - > **RENTAL:** sturdy cabinets with versatile audio inputs
 - > **STAGE MONITOR:** clear voice with low acoustic feedback
 - > CLUBS, BARS, PRO DJs, ...: Incredible "hifi" sound, even at high SPL
- **Bi-Amping "Pascal Audio®" amplifier technology** for maximum reliability and impact:
 - > HF: 150Wrms (1" compression driver with 80°H x 40°V, made by "Redcatt®" USA)
 - > LF: 500Wrms (12" woofer, made by "Lavoce®" Italy)
- > **DSP-controlled** amplifier with different presets:
 - Parametric EQs
 - > Limiter / compressors
 - Active 2-way crossover with FIR filtering
 - > Factory presets for different applications
 - > Sophisticated amplifier temperature management
 - > Software and presets are upgradeable.
 - > Fully tuned 4-Band parametric EQ for perfect sound

> Two mixable input channels:

- > CH1: LINE level, balanced (XLR / Jack 6.3mm) & unbalanced (RCA / cinch)
- > CH2: different levels:
 - Balanced MIC (XLR / Jack 6.3mm)
 - Balanced MIC with High pass filter
 - > Balanced LINE input (XLR / Jack 6.3mm)
- > 2 audio outputs:
 - > LINK OUTPUT for CH1
 - > MIXED OUTPUT: link to other speakers
- > Max. SPL: 129dB @ 1m
- > PowerCON in/out with separate power switch.
- > 6 Rigging points M6 for horizontal / vertical suspension.
- > 1st choice Baltic birch plywood with scratch free black textured Polyurea finishing.
- > Ingenious cabinet design allows for use as monitor without separate stands.
- > Heavy duty carrying handles with integrated 35mm stand adapter.
- > Heavy duty rubber feet.









TECHNICAL SPECIFICATIONS

General : Dimensions (cm) $65.3 \times 37.1 \times 37$

General: Weight (kg) 20

General : Powerinput AC 100 - 240V, 50/60Hz

General : Energy LabelNoGeneral : ColorblackGeneral : FixationM6General : IP ratingindoorAudio : max. spl (dB)129Audio : min. frequency (Hz)41Audio : max. frequency (Hz)25000Audio : Wrms 8Ω stereo, per channel650

Audio : functionsadjustable crossover, DSP, limiterConnections : input3 pin XLR, rca, usb, PowerCon® or

Connections : input compatible


Connections : output3 pin XLR, PowerCon® or

Brand compatible SYNQ

EANCode 5420025686051

SKU B08605





SA-12

YOUR DEALER

