

SQT-210

DESCRIPTION

Premium class DSP-processed active speaker cabinet with 2x 10" LF + 1.4" MID/HF driver, designed for a wide range of professional high SPL applications

FEATURES

- Professional active speaker cabinet for a wide range of different applications:
 - **RENTAL:** sturdy cabinets with versatile audio inputs
 - **STAGE:** perfect solution for music bands who want a compact but powerful audio system
 - **CLUBS, BARS, PRO DJs, ...** : Incredible „hifi“ sound, even at high SPL
- **Bi-Amping “Pascal Audio®” amplifier technology** for maximum impact: LF 810W + MID/HF 810W RMS-power.
- **DSP-controlled** amplifier with different presets:
 - Parametric EQs
 - Limiter / compressors
 - Active 2-way crossover with **FIR filtering**
 - Factory presets for different applications
 - Sophisticated amplifier temperature management
 - Software and presets are upgradeable.
 - Fully tuned 4-Band parametric EQ for perfect sound
- SPL: 136dB @ 1m
- Perfect for both permanent installations and portable use (Rental, Bands, DJ, ...).
- Equipped with high power woofers & compression driver:
 - LF: 2x 10" long excursion woofers
 - MID/HF: 1.4" B&C compression driver (3" voice coil)
- Rotatable 70°x 40° constant directivity horn.
- Two mixable input channels:
 - CH1: Balanced LINE input (XLR / Jack 6.3mm) & unbalanced (RCA / cinch)
 - CH2: Balanced LINE input (XLR / Jack 6.3mm)
- 2 audio outputs:
 - LINK OUTPUT with only the CH1-signal
 - MIXED OUTPUT: link to other speakers
- PowerCON in/out with separate power switch.
- Different rigging option for horizontal / vertical suspension.
- Special quick-mount U-bracket (optional):
 - Easy TRUSS mounting with PAN/TILT possibility
 - Pole mount with PAN/TILT possibility
 - Handles on top/bottom with internal 38mm speaker stand adapter
- 1st choice Baltic birch plywood with scratch free black textured Polyurea finishing.
- Combines perfectly with:
 - 1 or 2 SA-B15 active subwoofers
 - SQ-215 and SQ-218 passive subwoofers (extra amplifier / filter needed)
- Heavy duty rubber feet.



TECHNICAL SPECIFICATIONS

General : Dimensions (cm)	70 x 33 x 40
General : Weight (kg)	28
General : Powerinput	AC 100 - 240V, 50/60Hz
General : Energy Label	No
General : Color	black
General : IP rating	indoor
Audio : max. spl (dB)	136
Audio : min. frequency (Hz)	40
Audio : max. frequency (Hz)	20000
Audio : Wrms 8Ω stereo, per channel	1620
Audio : functions	adjustable crossover, DSP, limiter
Connections : input	3 pin XLR, rca, usb, PowerCon® or compatible
Connections : output	3 pin XLR, PowerCon® or compatible
Brand	SYNQ
EANCode	5420025686150
SKU	B08615



YOUR DEALER



WWW.SYNQ-AUDIO.COM | WWW.FACEBOOK.COM/SYNQ.AUDIO

BEGLEC NV HAS THE RIGHT TO CHANGE PRODUCTS AND SPECIFICATIONS WITH AND WITHOUT NOTICE. MAJOR AS WELL AS MINOR CHANGES CAN BE INVOLVED. THIS LEAFLET CAN CONTAIN ERRORS, THEREFORE WE ADVISE TO CONSULT YOUR LOCAL DEALER TO ENSURE THAT ACTUAL FEATURES AND SPECIFICATIONS MATCH YOUR REQUIREMENTS. COPYRIGHT © 2023 BY BEGLEC NV. ALL RIGHTS RESERVED.