BTX-SATURN

04428

DESCRIPTION


270W LED-moving head with 8-45° zoom, CMY-color mixing, CTO, CTB, UV, Iris, Frost, gobo morphing, ...

FEATURES

- High efficiency moving head projector based on a powerful 270W LED engine!
- Wide range electronic zoom, from 8° to 45° + motorized focus.
- Silence mode for theater applications.
- Fast 540° pan and 270° tilt movements.
- 16bit resolution pan/tilt resolution with position correction and pan/tilt speed channel.
- CMY color mixing to create lots of saturated and pastel colors.
- 9 extra fixed colors including 2 CTO, one CTB and UV.
- 7 replaceable rotating gobos with fine indexing.
- 9 fixed static gobos for gobo morphing.
- Rotating 3 facets prism.
- Iris module for dynamic effect.
- Variable frost filter for perfect wash effect.
- Aperture diaphragm for excellent logo projection.
- Opening/closing pulse, ramp and random effects on zoom, iris and frost channels.
- Four dimmer curves: linear, square, inverse square, S-curve, fast and slow dimming mode.
- Accurate strobe with built in random, pulse and burst effects.
- 3 focus compensate distances to always keep the focus according to the zoom opening.
- Uses 25 or 27 DMX channels + RDM-functionality for easy remote setup
- Easy USB firmware update to keep the moving head up-to-date at all times.
- The matrix LCD-display assures easy navigation in the different setup menus
- 3 & 5pin DMX in/outputs + Neutrik PowerCON TRUE1 in/outputs for easy daisy chaining.
- Equipped with omega brackets for fast installation.













www.briteq-lighting.com | https://www.facebook.com/Briteq

TECHNICAL SPECIFICATIONS

General : Application Stage & Rental, Theatre

General: Dimensions (cm) see drawing

General: Weight (kg) 21.5

General : Powerinput AC 100 - 240V, 50/60Hz

General: Energy Label No
General: Power consumption W 392
General: Color black
General: Display LCD

General: Fixation included omega bracket

General: IP rating indoor **Control: manual** No Control: Master/Slave No **Control: SMART-DMX** No **Control: Standalone** no **Control: programmable** No **Control: upgradable software** Yes **Control: maximum DMX channels** 27 **Light: lamp socket** none

Light : Lux 31680 (@5m, beam 8°)

Light: lumen 18750
Light: lamp LED
Light: min. color temperature (K) 3200
Light: max. color temperature (K) 8000
Light: colors other
Light: mix colors Yes
Light: fixed gobos 9
Light: rotating gobos 7

Light : focusMotorizedLight : zoomMotorizedLight : irisYes

Light : prism (# facets + rotating y/n 3-facet, rotating

Light: frost filter

Light: min. beam angle (°)

Light: max. beam angle (°)

Light: min. refresh rate (kHz)

Light: max. refresh rate (kHz)

1.2

Connections : input3 pin XLR, 5 pin XLR, TRUE1 powerCON, usb, rdm

powerCON, usb, rdm 3 pin XLR, 5 pin XLR, TRUE1

Connections : output powerCON, rdm

Brand BRITEQ

EA NCode 5420025644280

Discontinued No

