

WTR-DMX TRANSCIVER

IP MK2

DESCRIPTION

Outdoor IP65 wireless DMX-transceiver (transmitter + receiver), compatible with both LumenRadio® and Wireless Solution®. Robust enclosure for fixed install and stage applications.

FEATURES

- The perfect solution when wireless DMX with maximum flexibility and reliability is needed!
- IP65 transceiver (sender or receiver mode) for both architectural and stage applications.
- **Compatible with LumenRadio® CRMX and Wireless Solutions® W-DMX™ protocols:**
 - **Transmitter mode:** CRMX classic + W-DMX™ G3 / G4S
 - **Receiver mode:** CRMX² / CRMX classic + W-DMX™ G3 / G4 / G4S / G5
- 5dBi antenna for better signal reception/transmitting!
- 2.4GHz band for worldwide license free use!
- RDM compatible (in RX-mode).
- Up to 150m of safe working distance!
- Robust black die-cast aluminum weatherproof housing for outdoor use.
- Lockable IP65 power input/output connectors (Neutrik PowerCON® TRUE1 compatible).
- Seetronic IP65 XLR 3pin in/out for easy daisy chaining (5pin XLR in/out possible).
- Fully CE / RED certified!

NOTE: This product has IP65 rating while used for non-permanent outdoor installation and under normal conditions (not exposed to seawater).



TECHNICAL SPECIFICATIONS

General : Dimensions (cm)	23 x 16 x 8
General : Weight (kg)	2.1
General : Powerinput	AC 100 - 240V, 50/60Hz
General : Energy Label	No
General : Power consumption W	1
General : Color	black
General : Display	LED
General : Fixation	optional omega bracket
General : RU	No
General : IP rating	outdoor
Control : Protocol	DMX, Wireless DMX, RDM
Control : programmable	No
Control : upgradable software	Yes
Control : minimum DMX channels	1
Control : maximum DMX channels	512
Connections : input	3 pin XLR, wireless DMX, PowerCon® TRUE1 or compatible
Connections : output	3 pin XLR, PowerCon® TRUE1 or compatible
Brand	BRITEQ
EANCode	5420025650410
SKU	B05041



YOUR DEALER

