## BT-VERTIGO

## DESCRIPTION

Compact moving wash equipped with 7x60W RGBL LEDs, extremely fast Pan/Tilt/Zoom movements & large  $4^{\circ}$ - $70^{\circ}$  zoom range

## **FEATURES**

- > BT-VERTIGO is a small and very powerful moving wash projector.
- > Based on 7x60W RGBL LED light sources.
- Very high and extremely stable light output: 11555 lux @5m (4°) 201 lux @5m (45°).
- Perfect for: Fast-moving effects and projection of very evenly colored beams
- > Wide range 16bit electronic zoom, from 4° to 45°.
- > High quality CCT presets: 2700K → 8000K (CRI >80).
- Accurate strobe with built in random, pulse and burst effects.
- > Smooth 16bit dimmer with fast and slow dimming mode.
- > Two dimmer curves: linear, square.
- Super fast 16bit pan/tilt/zoom movements with position correction and pan/tilt speed channel.
- > Silent fan mode for theater applications.
- Uses 17, 23 or 21 DMX channels + RDM-functionality for easy remote setup.
- > The matrix LCD-display assures easy navigation in the different setup
- > 5pin DMX in/outputs + PowerCON TRUE1 compatible.
- > DMX in/outputs can be converted to XLR 3pin with BT-XLR5TO3 kit.
- > Equipped with an omega bracket for fast installation.









## TECHNICAL SPECIFICATIONS

**General**: Dimensions (cm) 25 x 16.5 x 38.4

**General**: Weight (kg) 6.25

**General: Powerinput** AC 100 - 240V, 50/60Hz

**General: Energy Label** No **General: Power consumption W** 300 **General**: Color black **General**: Display LCD

included omega bracket **General: Fixation** 

**General: IP rating** indoor

standalone fixed, standalone **Control: Modes** automatic, manual, DMX

**Control: Protocol** DMX, RDM

**Control: programmable** No **Control: upgradable software** Yes **Control: minimum DMX channels** 17 **Control: maximum DMX channels** 23 **Light: lamp socket** No

**Light: Lux** 11555 lux @5m (beam 4°)

Light: lumen 2940 **Light: lamp** LED **Light: min. color temperature (K)** 2700 **Light:** max. color temperature (K) 8000 Light : CRI 80 **Light: colors** 

Lime, RGBL

**Light:** mix colors Yes

**Light: functions** motorized zoom

**Light**: min. beam angle (°) 45 **Light**: max. beam angle (°) Light: max. refresh rate (kHz) 4.8

5 pin XLR, rdm, PowerCon® **Connections: input** 

TRUE1 or compatible

5 pin XLR, rdm, PowerCon® **Connections: output** TRUE1 or compatible

**Brand** BRITEQ

**EANCode** 5420025655859

SKU B05585





