BTI-AKKUPOLE WHITE

DESCRIPTION

Stylish IP64 OUTDOOR battery-powered 4x 5Watt LED-lighting pole with wireless DMX, perfect to light up garden parties, buffets, presentation counters, etc.

FEATURES

- Stylishly designed battery-powered lighting pole with great autonomy.
- > The ultimate IP64 OUTDOOR upgrade of our highly successful BT-AKKUPOLE: no more stress if a sudden rain shower hits!
- > The perfect tool for illuminating outdoor events, buffets, presentation counters, etc.
- > Equipped with 4 pivoting 5 watt 25° LED projectors (3000K & CRI>90).
- > The sturdy swivel arm with projectors can be set in 6 fixed positions.
- > Lightning-fast assembly/disassembly without any tools.
- > Sturdy construction quality with adjustable height for frequent and versatile use in rental jobs.
- > The supplied heavy base (45x37cm) ensures very high stability, even at maximum height.
- > Equipped with magnetic filter holders for the use of all kinds of filters:
 - > CTO/CTB filters: adjust CCT to e.g. 4000K, 2700K, ...
 - > Color filters: choose any color imaginable
 - > Frost filters: adjust beam angle
- > Clear and very easy user interface.
- > 3 touch buttons and clear LCD screen with information about remaining battery time.
- > Multiple operating modes:
 - Built-in wireless DMX receiver (with XLR output: can serve as W-DMX receiver)
 - Wired DMX control via XLR in/out (1 dimming channel)
 - > Simple manual operation on the base
- > High-capacity lithium batteries (288Wh) for extended autonomy (>14.5 hours at 100% output).
- Internal processor-controlled battery charger with IP65 in/output power connectors.
- > The standard waterproof XLR 3pin in/out connectors can be changed to XLR 5pin in/out.
- > Available in both BLACK and WHITE version: adapts perfectly to any venue!
- > Works perfectly on mains power as well (batteries are recharged during use).
- > Professional flight case (120x60cm) optionally available for transport of 4 complete sets.











TECHNICAL SPECIFICATIONS

General: Dimensions (cm) see picture

General: Weight (kg) 25

General: Powerinput AC 100 - 240V, 50/60Hz, Battery

General: Works on battery General: Energy Label No **General: Power consumption W** 69 **General**: Color white LCD **General: Display General: IP rating** outdoor

standalone fixed, manual, DMX, **Control: Modes**

Master/Slave **Control: Protocol** DMX, Wireless DMX

Control: programmable No **Control: upgradable software** No **Control: minimum DMX channels** 1 **Control: maximum DMX channels** 1 **Light: lamp socket** No **Light: lamp LED Light**: min. color temperature (K) 3200 **Light:** max. color temperature (K) 3200 Light: CRI

Light: colors Warm white

Light: mix colors No **Light**: min. beam angle (°) 25 **Light**: max. beam angle (°) 50 **Light**: max. refresh rate (kHz) 4.3

3 pin XLR, wireless DMX, **Connections: input**

PowerCon® TRUE1 or compatible

3 pin XLR, wireless DMX, **Connections: output**

PowerCon® TRUE1 or compatible

Brand BRITEQ

EANCode 5420025651868

SKU B05186











