

# BT-THEATRE 150EZ

## Mk3

### DESCRIPTION

Very powerful 150Watt LED theater spot with motorized 12.5° to 56.2° zoom and excellent very low noise cooling. Behaves like a halogen Fresnel, thanks to redshift / amber drift effect!



### FEATURES

- Extremely powerful LED theater spot with electronic zoom: 12.5° to 56.2° beam angle.
- The 150W warm white 3200K LED produces an incredible light output that even easily outperforms traditional 1kW halogen theatre projectors!
- **This new Mk3-version with redshift / amber drift effect, behaves exactly like a traditional halogen Fresnel!**
- Excellent photometric characteristics: CRI / Ra >97, TLCI >97, CQS >95, Rf >95, R9 >97 !
- Color frame for use of color filters and eight-leaf barndoor included.
- No more heavy and expensive dimmer packs needed!
- Reworked cooling system for extremely silent operation, low LED temperature and very stable light output.
- LCD-display to navigate easily through the reworked setup menu!
- DMX-controlled: 7 different channel modes (8bit and 16bit dimming) for maximum flexibility.
- Prepared for wireless DMX: just plug-in an optional WTR-DMX DONGLE !
- Flicker free TV-recordings & no high-pitch dimmer noises, thanks to HF PWM dimming: up to 20kHz !
- Manual dimming & zoom/focus control: easy projector alignment on the stage + use on exhibition booths.
- The lamp behavior can be continuously adjusted from led to halogen.
- Four dimmer curves: linear, square, inverse square, S-curve.
- In case of DMX failure, you can choose between blackout and freeze mode.
- RDM-functionality for easy remote setup: DMX addressing, channel mode, ...
- Lock function to avoid unwanted altering of the settings.
- Default factory settings + user settings can be saved/loaded.
- 3 & 5pin DMX in/outputs + **PowerCON TRUE1** compatible in/outputs for easy daisy chaining.
- The hanging bracket can be equipped with our “omega bracket small”.




TECHNICAL SPECIFICATIONS

General : Dimensions (cm)	See drawing
General : Weight (kg)	9.8
General : Powerinput	AC 100 - 240V, 50/60Hz
General : Energy Label	No
General : Power consumption W	160
General : Color	black
General : Display	LCD
General : Fixation	optional omega bracket, M12
General : IP rating	indoor
Control : Modes	standalone fixed, manual, DMX, Master/Slave
Control : Protocol	DMX, Wireless DMX, RDM
Control : programmable	No
Control : upgradable software	Yes
Control : minimum DMX channels	1
Control : maximum DMX channels	9
Light : lamp socket	No
Light : Lux	3141 (@ 5 meter, beam 12.5°)
Light : lumen output max (lm)	9178
Light : lamp	COB
Light : min. color temperature (K)	3150
Light : max. color temperature (K)	3250
Light : CRI	97
Light : colors	Warm white
Light : mix colors	No
Light : functions	motorized zoom
Light : zoomrange	12.5° - 56.2°
Light : max. refresh rate (kHz)	20
Connections : input	3 pin XLR, 5 pin XLR, wireless DMX optional, usb, rdm, PowerCon® TRUE1 or compatible
Connections : output	3 pin XLR, 5 pin XLR, PowerCon® TRUE1 or compatible
Brand	BRITEQ
EANCode	5420025660594
SKU	B06059



YOUR DEALER



WWW.BRITEQ-LIGHTING.COM | WWW.FACEBOOK.COM/BRITEQ

BEGLEC NV HAS THE RIGHT TO CHANGE PRODUCTS AND SPECIFICATIONS WITH AND WITHOUT NOTICE. MAJOR AS WELL AS MINOR CHANGES CAN BE INVOLVED. THIS LEAFLET CAN CONTAIN ERRORS, THEREFORE WE ADVISE TO CONSULT YOUR LOCAL DEALER TO ENSURE THAT ACTUAL FEATURES AND SPECIFICATIONS MATCH YOUR REQUIREMENTS. COPYRIGHT © 2025 BY BEGLEC NV. ALL RIGHTS RESERVED.