

04649

DESCRIPTION

4 channel direct control chain hoist motor controller with separate UP/DOWN-controls and master/slave linking.

FEATURES

- Standalone chain hoist motor controller.
- Controls up to 4 motors in standalone operation
- Several units can be linked in master/slave using the link in/out on the back panel:
 - Easy control for a larger number of chain hoists.
 - Simultaneous hoist control using the UP/DOWN buttons on the master controller.
 - Centralized Emergency stop on the master controller.
 - "Slave" indicator led.
- Manual phase inversion switch for each output.
- Choice of different outputs for maximum flexibility (rental companies!):
 - 4x individual CEE16 4pole 16A outputs
 - 1x 16PIN multichannel industrial rectangular connector, Harting® compatible
 - 1x 19PIN multichannel industrial round connector, Socapex® compatible
 - 1x earthed 16A mains outlet: auxiliary output for all kinds of use.
- Remote control input (XLR) with led indicator to connect the [RICO-REMOTE] (optional, order code: 4650).
- Phase indicators to easily check if the 3phases are available.
- 32A 4pole circuit breaker protects ALL outputs, including the 32A output to the next unit. In case of emergency all 3 phases AND the neutral are disconnected.
- Two C16 (16A 1P+N) 2-POLE automatic circuit breakers for control circuit + auxiliary output.
- Mains input cable (3x 32A, 5wire), equipped with CEE (3P+N+E) 32A inlet plug
- CEE (3P+N+E) outlet socket (3x 32A, 5wire) for bypass
- Extremely robust 19"/4U metal housing.
- Designed and build in Europe to the highest international safety standards!







SPECIFICATIONS

General : Application Stage & Rental, Theatre General : Dimensions (cm) 48,2 x 18,4 x 37,4 cm

General: Weight (kg) 13.5
General: Color black
Stand & Truss: tube Ø No
Stand & Truss: truss type other
Brand BRITEQ

EA NCode 5420025646499

Discontinued









