


Condenser Headset Microphones



Headset Microphone

- ① Gooseneck
- ② Adjustable Headband
- ③ 4 Pin Mini XLR
- ④ 4 Pin Hirose Connector (Option)
- ⑤ 3 Pin Mini XLR (Option)
- ⑥ 3.5 Stereo Plug (Option)
- ⑦ Windscreen



CM-214i Lightweight Headset Microphone




- * Comfortable, lightweight and confident.
- * Omni-directional pick up pattern .
- * Smooth frequency response.
- * No proximity effect.
- * High quality steel headband assures durability, mini gooseneck for best position.
- * Adjustable headband.
- * A drip ring is offered.
- * Carry pouch is provided.
- * Detachable cable.

Available Color : Beige
Black

CM-214Ui Uni-direction Lightweight Headset Microphone

The CM-214Ui is of a low profile headband as CM214i

Model No.	CM-214i	CM-214Ui
Frequency Response	60 ~ 15,000Hz	30 ~ 18,000Hz
Polar Pattern	Omni-directional	Cardioid
Sensitivity @ 1 KHz	-60±3dB *(1mV)*0dB=1V/μbar	-68±3dB *(0.4mV)*0dB=1V/μbar
Impedance	1.8kΩ	680Ω
max. SPL for 1% T.H.D.	130dB	130dB
Connector Type	4 Pin Mini XLR	4 Pin Mini XLR
Standard Accessories	Windscreen	Windscreen



CM-214ULi Lightweight Unidirectional Headset Microphone

- * Comfortable, lightweight and confident.
- * Uni-directional pick up pattern.
- * Smooth frequency response.
- * High quality steel headband assures durability, mini gooseneck for best position.
- * Adjustable headband.
- * Bundled with three detachable cables.
- * Carry pouch is provided
- * Detachable cable.

Available Color : Beige
Black

CM-235i Subminiature Headset Microphone

- * For theatre, live sound, TV and musicals.
- * Omni-directional.
- * Excellent acoustic performance.
- * Very comfortable to wear.
- * High quality mini gooseneck assures best miking position.
- * Adjustable headband.
- * Detachable cable.

Available Color : Beige
Black

Model No.	CM-214ULi	CM-235i
Frequency Response	100 ~ 18,000Hz	50 ~ 18,000Hz
Polar Pattern	Cardioid	Omni-directional
Sensitivity @ 1 KHz	-65±3dB *(0.56mV)*0dB=1V/μbar	-53±3dB *(2.24mV)*0dB=1V/μbar
Impedance	1.8kΩ	1.8kΩ
max. SPL for 1% T.H.D.	120dB	130dB
Connector Type	4 Pin / 3 Pin Mini XLR 3.5 Stereo Plug	4 Pin Mini XLR
Standard Accessories	Windscreen	Windscreen

Condenser Headset Microphones