

Key features

- Ultra-compact
- Versatile sound reinforcement
- High performance
- 90° x 90° wide dispersion
- ARK processor optimised preset
- Multiple rigging / mounting options

Applications

- Club & Bar installations
- Sound reinforcement
- Theatres
- Houses of worship
- Multi media spaces
- Public address



General description & specs

High performance, ultra-compact, full range, two way passive cabinet.

It consists of a 6.5" transducer (impedance 16 ohm) and a 1" high frequency Mylar tweeter.

It offers 119 dB SPL (400 W program)

Components	LF: 1 x 6.5" - 2" voice coil	Rated Power (AES)	200 W (400 W program, 800 W peak)
	HF: 1 x Tweeter 1" - 1.25" aluminium voice coil, Mylar diaphragm	Crossover	Passive
		Nominal Impedance	16 Ohms
Frequency Range	62Hz – 20 KHz (-10dB)	Connectors	2 x Neutrik Speakon NL4MP / 4 x Terminal Block 7.62 mm between pins
Frequency Response	88Hz – 18 KHz (± 3dB)	Finish	High resistant Polyurea coating
Sensitivity	93 dB (1W@1m)	Material	15 mm Premium birch plywood
Max. SPL	116 dB – 122 dB Peak	Dimensions (H x W x D)	300 x 236 x 220 mm
Coverage	90° H x 90° V	Weight	7.5 Kg (17 lbs)