

Key features

- Ultra-compact
- Versatile sound reinforcement
- High performance
- Dispersion 90° x 60° rotatable
- ARK processor optimised preset
- Multiple rigging / mounting options

Applications

- Club & Bar installations
- Sound reinforcement
- Theatres
- Houses of worship
- Multi media spaces
- Public address



General description & specs

High performance, ultra-compact, full range, two way passive cabinet.

It consists of a 8" transducer with Neodimium magnet and a 1" high frequency compression driver.

It offers 125 dB SPL (600 W program)

Components	LF: 1 x 8" Neodimium - 2" alu voice coil kapton cone	Rated Power (AES)	300 W (600 W program, 1200 W peak)
	HF: 1" Exit compression Driver, 1.75" aluminium voice coil, Polyester diaphragm	Crossover	Passive
		Nominal Impedance	8 Ohms
Frequency Range	60Hz – 20 KHz (-10dB)	Connectors	2 x Neutrik Speakon NL4MP / 4 x Terminal Block 7.62 mm between pins
Frequency Response	78Hz – 18 KHz (± 3dB)	Finish	High resistant Polyurea coating
Sensitivity	97 dB (1W@1m)	Material	15 mm Premium birch plywood
Max. SPL	122 dB – 128 dB Peak	Dimensions (H x W x D)	420 x 274 x 298 mm
Coverage	90° x 60° Rotatable	Weight	10 Kg (22 lbs)