



## ARK803MP

Wall mounted column loudspeaker, 200W AES, 120dB SPL

- Mid frequency: 8x3" midrange / 0.75" v.c.
- Frequency response: 135-17000 Hz ( $\pm 3$ dB)
- Coverage angle HxV: 115x20°
- The modules with 8 transducers of 3" represent the solution to sound in deep environments particularly difficult, where quality and intelligibility are required.
- Column modules with an off-axis transducer for wide horizontal dispersion.
- Aluminium frame for a very robust yet lightweight design that fits in with any environment.

### Versions:

**ARK803MPBK** (Black finish)

**ARK803MPWH** (White finish)

# ARK803MP



8x3"



115°x20°



WALL MOUNT

## ARK803MP TECHNICAL DATA

### LOUDSPEAKERS

- System type: column loudspeaker

### COMPONENTS

- Mid frequency: 8x3" midrange / 0.75" v.c.

### FEATURES

- AES/program power: 200/400W
- SPL max: 120dB @1m (free field)

### ACOUSTICAL SPECIFICATIONS

- Sensitivity: 95dB @1W/1m (free field)
- Impedance: 16 Ohm
- SPL cont/peak: 114/120dB @1m (free field)
- Frequency response: 135-17000Hz ( $\pm 3$ dB)
- Coverage angle HxV: 115x20°
- Suggest HPF range: 140/180Hz
- Recommended amplifier up to: 400W /16Ohm

### INPUT/OUTPUT CONNECTORS


- Input signal: XLR IN/OUT, pin RCA unbal.

### CABINET CONSTRUCTION

- Cabinet material: 3mm aluminum die cast
- Suspension system: wall brackets (included)

### PHYSICAL

- Dimensions (WxHxD): 110x690x148mm
- Weight: 7.5kg



The brackets allow a rotation on the horizontal plane of 180° to step of 15° and a tilt on the vertical plane of 30° to 8° step.



Screw for the rotation on the horizontal plane.