



## LUMIPAR12IP

- Source: 12x9W RGBW LEDs
- Luminous flux: (D20) 3900 lm (D45) 6700lm
- Beam angle: Available in 20° or 45°
- Colour mixing: RGBW/FC
- Colour wheel: virtual colour wheel with presets
- Protocols: DMX512
- DMX channels: 4/6/11 channel
- Power consumption (at 230V): 110W
- Output (at 230V): 33 units on a single power line
- Signal connection: Seetronic XLR 5p IN/OUT connectors
- Power connection: Seetronic powerKon waterproof IN/OUT connectors
- IP rating: 65 for outdoor events
- Dimensions (WxHxD): 305x326x177mm
- Weight: 6.2kg

### Variants

#### LUMIPAR12IP20D

Beam Angle: 20°

#### LUMIPAR12IP45D

Beam Angle: 45°



## LUMIPAR7IP

- Source: 7x9W RGBW LEDs
- Luminous flux: (D20) 2945 lm (D45) 3835lm
- Beam angle: Available in 20° or 45°
- Colour mixing: RGBW/FC
- Colour wheel: virtual colour wheel with presets
- Protocols: DMX512
- DMX channels: 4/6/11 channel
- Power consumption (at 230V): 65W
- Output (at 230V): 58 units on a single power line
- Signal connection: Seetronic XLR 5p IN/OUT connectors
- Power connection: Seetronic powerKon waterproof IN/OUT connectors
- IP rating: 65 for outdoor events
- Dimensions (WxHxD): 240x286x154mm
- Weight: 3.64kg

### Variants

#### LUMIPAR7IP20D

Beam Angle: 20°

#### LUMIPAR7IP45D

Beam Angle: 45°



## VERSAPAR

- Source: 12x10W RGBW LEDs
- Luminous flux: (10°) 1223 - (60°) 1423lm
- Zoom: 10-60° motorised linear zoom
- Colour mixing: RGBW/FC
- Colour wheel: virtual colour wheel with presets
- Protocols: DMX512
- DMX channels: 5/7/10 channel
- Power consumption (at 230V): 121W
- Output (at 230V): 12 units on a single power line
- Signal connection: XLR 3p+5p IN/OUT connectors
- Power connection: Neutrik powerCON IN/OUT connectors
- IP rating: 30
- Dimensions (WxHxD): 262x350x261mm
- Weight: 5.5kg