



WIFIUSB
(optional)

LUMIPARIRCH
(optional)

LUMIPAR12UTRI

- Source: 12x3W RGB LEDs
- Luminous flux: 1167lm
- Beam angle: 16°
- Colour mixing: RGB/FC
- Colour wheel: virtual colour wheel with presets
- Sound mode: music activation through internal microphone and sensitivity control
- Protocols: DMX512
- DMX channels: 3/8channel
- IR: infrared sensor controlled by remote
- Power consumption (at 230V): 35,5W
- Output (at 230V): 35 units on a single power line
- Data: USB port for USB WIFI transmitter (optional)
- Signal connection: XLR 3p IN/OUT connectors
- Power connection: IEC IN/OUT connectors
- IP rating: 20
- Dimensions (WxHxD): 226x184x220mm
- Weight: 1.8kg

LUMIPACK12UTRI

Lighting kit composed of 4 LUMIPAR12UTRI, nylon bag, DMX/power cable, IRC remote



WIFIUSB
(optional)

LUMIPARIRCH
(optional)

LUMIPAR7UTRI

- Source: 7x3W RGB LEDs
- Luminous flux: 681lm
- Beam angle: 16°
- Colour mixing: RGB/FC
- Colour wheel: virtual colour wheel with presets
- Sound mode: music activation through internal microphone and sensitivity control
- Protocols: DMX512
- DMX channels: 3/7channel
- IR: infrared sensor controlled by remote
- Power consumption (at 230V): 20W
- Output (at 230V): 57 units on a single power line
- Data: USB port for USB WIFI transmitter (optional)
- Signal connection: XLR 3p IN/OUT connectors
- Power connection: IEC IN/OUT connectors
- IP rating: 20
- Dimensions (WxHxD): 183x141x179mm
- Weight: 1.2kg

LUMIPACK7UTRI

Lighting kit composed of 4 LUMIPAR7UTRI, nylon bag, DMX/Power cables, IRC remote



WIFIUSB
(optional)

LUMIPARIRCH
(optional)

QUADRO18UTRI

- Source: 18x3W RGB LEDs
- Luminous flux: 2040lm
- Beam angle: 13°
- Colour mixing: RGB/FC
- Protocols: DMX512
- DMX channels: 3/5/9/13channel
- Pixel control: section control
- W-DMX: optional, proprietary protocol compatible with WIFIBOX, WDBOX
- IR: infrared sensor controlled by remote
- Power consumption (at 230V): 51.5W
- Output (at 230V): 24 units on a single power line
- Data: USB port for USB WIFI transmitter (optional)
- Signal connection: XLR 3p IN/OUT connectors
- Power connection: IEC IN/OUT connectors
- IP rating: 20
- Dimensions (WxHxD): 395x260x44mm
- Weight: 3.4kg

