



## MINIRUBY

MINIRUBY is an ultra-compact beam light that harnesses all the power of its Osram Sirius 132W lamp into a tight, bright and sharp 3.5° beam. Its small form factor is designed to allow the users to apply a discharge beam light in tight locations or low ceilings bringing a big punch to a small space.

### LIGHT SOURCE

- Source: 132W Osram Sirius HRI
- CT: 9200K
- CRI: 60
- Luminous flux: 5150lm

### OPTICS

- Beam angle: 3,5°

### COLOUR SYSTEM

- Colour wheel: 9 dichroic filters + open

### DYNAMIC EFFECTS

- Circular prism: 8f with bi-directional rotation

### CONTROL

- Protocols: DMX512, RDM
- DMX channels: 7 / 9channel

### ELECTRICAL

- Power consumption (at 230V): 176W
- Output (at 230V): 12 units on a single power line

### PHYSICAL

- Signal connection: Amphenol XLR 3p + 5p IN/OUT connectors
- Power connection: Neutrik powerCON IN/OUT connectors
- IP rating: 30
- Dimensions (WxHxD): 278x387x200mm
- Weight: 7.6kg



### LIGHT SOURCE

132W Osram Sirius HRI



### BEAM ANGLE

3.5°



### CONNECTIVITY

DMX512, RDM



### IP RATING

20

