



## MZX1002

MZX1002 is a 2-Zone, 2U rack, equipped with 10 inputs and 2 assignable outputs.

### MATRIX MIXER

- Channels: 10 input - 2 output

### AUDIO SPECIFICATIONS

- Output level/impedance: 0dB/600Ohm balanced
- Frequency response: 20- 20000Hz @ 8 Ohm ( $\pm 0.5$  dB)
- THD+N:
- Input impedance: 20k $\Omega$
- Signal/Noise rate: >90dB

### POWER SUPPLY STAGE

- Operating voltage/frequency: 230 V AC (+/- 5%) / 24 V DC

### FUNCTIONS

- Input sensitivity: mic. (-60dB ~ -6dB), line (-30dB ~ +14dB)
- Tone controls input: 80 Hz, 2.5kHz, 12kHz ( $\pm 15$ dB)
- Tone controls output: 100 Hz, 10kHz ( $\pm 15$ dB)
- Phantom power: Mic.1, Mic.2, +18V

### INPUT/OUTPUT CONNECTORS

- Input signal: XLR/Jack bal. pin RCA unbal
- Output signal: XLR/Jack bal. pin RCA unbal.
- Power connection: VDE

### PHYSICAL

- Dimensions (WxHxD): 482x88x325mm
- Weight: 5.3kg



## MZX84

MZX84 is a 4-zone mixer, 2U rack, equipped with 8 inputs and 4 assignable outputs.

### MATRIX MIXER

- Channels: 8 input - 4 output

### AUDIO SPECIFICATIONS

- Output level/impedance: 0dB/600Ohm balanced
- Frequency response: 20- 20000Hz @ 8 Ohm ( $\pm 0.5$  dB)
- THD+N:
- Input impedance: 20k $\Omega$
- Signal/Noise rate: >90dB

### POWER SUPPLY STAGE

- Operating voltage/frequency: 100/240V, 50/60Hz

### FUNCTIONS

- Input sensitivity: mic. (-50dB ~ -6dB), line (-30dB ~ +14dB)
- Remote control: 0dB/600Ohm balanced
- Tone controls input: 80 Hz, 2.5kHz, 12kHz ( $\pm 15$ dB)
- Tone controls output: 80 Hz, 12kHz ( $\pm 15$ dB)
- Phantom power: ch1 - ch2/3/4 +15V

### INPUT/OUTPUT CONNECTORS

- Input signal: XLR/Jack bal. pin RCA unbal
- Output signal: moxex
- Data: RJ-45
- Power connection: VDE

### PHYSICAL

- Dimensions (WxHxD): 482x88x320mm
- Weight: 3.9kg