



## SUNRISE2L

- Source: 2x85W warm white LEDs
- CT: 3084K
- CRI: >82
- Luminous flux: 10464lm
- Beam angle: 65°
- Colour mixing: warm white
- Sound mode: music activation through internal microphone and sensitivity control
- Protocols: DMX512
- DMX channels: 1/2/4/7channel
- Pixel control: pixel2pixel control
- Power consumption (at 230V): 154W
- Output (at 230V): 24 units on a single power line
- Signal connection: XLR 3p+5p IN/OUT connectors
- Power connection: Seetronic powerKon IN/OUT connectors
- IP rating: 20
- Dimensions (WxHxD): 372x117x214mm
- Weight: 4.5kg



## SUNRISE2

- Source: 2x100W white COB LEDs
- CT: 3200K
- CRI: >80
- Luminous flux: 7156lm
- Beam angle: 50°
- Pixel patterns: pre-programmed dynamic and static patterns
- Protocols: DMX512
- DMX channels: 1/2/4/7channel
- Pixel control: pixel2pixel control
- Power consumption (at 230V): 155W
- Output (at 230V): 12 units on a single power line
- Signal connection: XLR 3p+5p IN/OUT connectors
- Power connection: Neutrik powerCON IN/OUT connectors
- IP rating: 30
- Dimensions (WxHxD): 473x105x270mm
- Weight: 6.8kg



## SUNRISE4

- Source: 4x100W white COB LEDs
- CT: 3200K
- CRI: >80
- Luminous flux: 18340lm
- Beam angle: 50°
- Pixel patterns: pre-programmed dynamic and static patterns
- Protocols: DMX512
- DMX channels: 4/6/9channel
- Pixel control: pixel2pixel control
- Power consumption (at 230V): 360W
- Output (at 230V): 6 units on a single power line
- Signal connection: XLR 3p+5p IN/OUT connectors
- Power connection: Neutrik powerCON IN/OUT connectors
- IP rating: 30
- Dimensions (WxHxD): 466x454x128mm
- Weight: 11.4kg