



# DISPLAYCOBTRWDFC

## LIGHT SOURCE

- Source: 60W COB RGB Led
- Luminous Flux: 2055lm
- Lux: (30°) 480lux @3m Full
- Lux: (60°) 178lux @3m Full
- Source Life Expectancy: >30.000 h

## OPTICS

- Beam Angle: 60°
- Field Angle: 80°
- Lens Type: Dichroic parabolic reflector in combination with HD fresnel lens
- Additional Optics: 30° (inc) - 15° (opt)

## COLOR SYSTEM

- Color Mixing: RGB/FC
- White Presets: 3200~10000K
- Color Wheel: Virtual color wheel with presets
- Macros: Built-in white presets

## DYNAMIC EFFECTS

- Static Color Mode: Selection of static color
- Manual Color Mode: Manual adjustment of color
- Auto Mode: Built-in programs with execution speed adjustment

## BODY

- Body: Sturdy die-cast aluminium body conceived for long-time durability
- Body Color: White

## CONTROL

- Protocols: DMX

- Dmx Channels: 3/5/8ch
- W-DMX: Included, Wireless Solution receiver
- Display: Black OLED high resolution display
- Firmware Upgrade: Yes, via USB-DMX interface (UPBOX1) not included
- Master/Slave: for synchronized operation of more units linked in a chain

## ELECTRONICS

- Dimmer: Linear 0~100% electronic dimmer
- Dimmer Curves: 4 Different dimming curves available
- Strobe/Shutter: 1-28 flash/s, electronic
- Operating Temperature: -10/45°
- Flicker: Flicker free operation

## ELECTRICAL

- Power Supply: 100-240V – 50/60Hz
- Power Consumption (at 230V): 75W
- Power Consumption (at 120V): 70W

## PHYSICAL

- Signal Connection: 5p in/out
- Power Connection: Track Adaptor (EUTRAC compatible)
- IP: 20
- Cooling: Natural cooling of the peculiar chassis and to absence of fans
- Suspension And Fixing: Track-Adapter included for suspension and fixing
- Dimensions (WxHxD): 166x118x290mm
- Weight: 1,85Kg



PHOTOMETRICS  
AND SPECIFICATIONS  
[WWW.MUSICLIGHTS.IT](http://WWW.MUSICLIGHTS.IT)



## Optional Accessories

**DISPLAYCOBBDWH:** Barndoor with 4 directional flaps to adjust the light beam, for DISPLAYCOB, WH

**DISPLAYCOBTPGWH:** Filter frame for DISPLAYCOB projectors, white

**DISPLAYCOBL15:** Optics for DISPLAYCOB projectors series, 15°

**UPBOX1:** Firmware Uploader Kit for PROLIGHTS products, USB IN, 3-pin XLR DMX OUT