



JETBEAM2

JETBEAM2 is an LED beam luminaire designed to be truly comparable to a discharge source. Ideal both for installation and for rental, the JETBEAM2 focusses on maximising the light output from its LED source, all the way throughout the glass optical system, to deliver a cutting-edge beam effect even on the brightest stage.

LIGHT SOURCE

- Source: 100W High Power White LED
- CT: 6300K
- CRI: 72Ra
- Luminous Flux: 1756lm

OPTICS

- Beam Angle: 2,5°

COLOR SYSTEM

- Color Wheel: 14 dichroic filters+Open

DYNAMIC EFFECTS

- Fixed gobos: 18 Fixed gobos+Open
- Circular Prism: 8f with bi-directional rotation, Indexing

CONTROL

- Protocols: DMX512, RDM
- DMX Channels: 9/11ch

ELECTRICAL

- Power Consumption (at 230V): 163W
- Output (at 230V): 26 units on a single power line

PHYSICAL

- Signal Connection: 3p+5p in/out
- Power Connection: PowerCON in/out
- IP: 20
- Dimensions (WxHxD): 303x421x230mm
- Weight: 13kg

Variants

JETBEAM2BK
Black housing

JETBEAM2WH
White housing



LIGHT SOURCE
100W High Power White LED



BEAM ANGLE
2,5°



UTILITY
DMX512, RDM

