

5x40 W moving head linear, pivot, mirror and pixel effect



Photometrics

Flux out: 591.2 lm

		\land		
3 ft / 1 m	9,172 / 12,210 fc		0.27 ft	
	98,725 / 131,429 lx		8.50 cm	
7640	2,293 / 3,052 fc		0.55 ft	
7 ft / 2 m	24,681 / 32,857 lx		17.01 cm	
	1,019 / 1,356 fc		0.83 ft	
10 ft / 3 m 13 ft / 4 m	10,969 / 14,603 lx		25.51 cm	
	573 / 765 fc		1.11 ft	
	6,170 / 8,241 lx		34.02 cm	
16 ft / 5 m 20 ft / 6 m	367 / 488 fc		1.39 ft	
	3,949 / 5,257 lx		42.52 cm	
	255 / 339 fc		1.67 ft	
20107 0111	2,742 / 3,651 lx		51.02 cm	
23 ft / 7 m	187 / 249 fc		1.95 ft	
	2,015 / 2,682 lx		59.53 cm	
26 ft / 8 m	143 / 191 fc		2.23 ft	
	1,543 / 2,054 lx		68.03 cm	
30 ft / 9 m	113 / 151 fc		2.51 ft	
	1,219 / 1,623 lx		76.53 cm	
	/			
Height	E avg / E max	Angle: 4.87°	Diameter	
Note: the Curves indicate the illuminated area and the				
average illumination when the luminaire is at different distance				

WEBSITE:www.prolights.it

MAIL: support@prolights.it

Technical specifications and data are provided for guidance only. We reserve the right to amend or alter at any time and without prior notice, the specification of any product. @Prolights

Air 5Fan - SINGLE LED (2°) Arolights

5x40 W moving head linear, pivot, mirror and pixel effect

Photometrics

Flux out: 176.4 lm

		\land		
3 ft / 1 m	2737 / 3.037 fc		0.27 ft	
	29,459 / 32,694	K	8.28 cm	
7 ft / 2 m 10 ft / 3 m	684 / 759 fc		0.54 ft	
	7,365 / 8,173 lx		16.56 cm	
	304 / 337 fc		0.81 ft	
	3,273 / 3,633 lx		24.83 cm	
13 ft / 4 m	171 / 190 fc		1.08 ft	
	1,841 / 2,043 lx		33.11 cm	
16 ft / 5 m	109 / 121 fc		1.35 ft	
	1,178 / 1,308 lx		41.39 cm	
20 ft / 6 m	76.02/ 84.37 fc		1.62 ft	
	818.3 / 908.2 lx		49.67 cm	
23 ft / 7 m	55.85 / 62 fc		1.90 ft	
	601.2 / 667.2 lx		57.94 cm	
26 ft / 8 m	42.76 / 47,45 fc		2.17 ft	
	460.3 / 510.8 lx		66.22 cm	
30 ft / 9 m	39,57 / 37,49 fc		2.44 ft	
	393.7 / 403.6 lx		74.50 cm	
Height	E avg / E max	Angle: 4.74°	Diameter	
Note: the Curves indicate the illuminated area and the				
average illumination when the luminaire is at different distance				

PROLIGHTS is a registered trademarks

WEBSITE:www.prolights.it

MAIL: support@prolights.it

Technical specifications and data are provided for guidance only. We reserve the right to amend or alter at any time and without prior notice, the specification of any product. @Prolights