

## SHARXS HTI 1200 W/D7/60

SharXS HTI | Metal halide lamps, double-ended



### Areas of application

- Concert and effect lighting

### Product family features

- High efficiency thanks to short-arc technology
- High thermal load capacity thanks to eXtreme Seal (XS) technology - enables high pinch temperatures of up to 450 °C
- Hot restart capability
- Compact modular design - the same dimensions for all wattages within each SharXS family
- Pre-focus base for accurate lamp installation



## Product datasheet

### Technical data


#### Electrical data

Nominal wattage	1200.00 W
Nominal voltage	95.0 V
Ignition voltage	5.0 / 35 kVp
Nominal current	12.7 A
Lamp current	12.7 A

#### Photometrical data

Nominal luminous flux	110000 lm
Luminance	41000 cd/cm <sup>2</sup>
Color temperature	6000 K
Color rendering index Ra	90

#### Dimensions & weight



Diameter	21.0 mm
Length	136.0 mm
Light center length (LCL)	57.5 mm

#### Temperatures & operating conditions

Maximum permitted pinch temperature	450 °C
-------------------------------------	--------

#### Lifespan

Lifespan	750 h
----------	-------

#### Additional product data

Base (standard designation)	SFc10-4
-----------------------------	---------

## Product datasheet

<b>Product remark</b>	Also available as an OEM package with 30 units without knurled nuts/XS = eXtreme Seal (maximum permissible foil temperature 450 °C)
-----------------------	---

### Capabilities

<b>Burning position</b>	Any
-------------------------	-----

### Certificates & standards

<b>EEI – Energy Label</b>	B
---------------------------	---

---


### Country specific information

Product code	METEL code	SEG-No.	STK-Number	UK Org
4008321285256	OSRHTI1200D760	-	-	-
4008321285263	OSRHTI1200D760	-	-	-

## Product datasheet

### Safety advice

Because of their high luminance, UV radiation and high internal pressure during operation, SharXS lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Appropriate filters must ensure that UV radiation is reduced to an acceptable level. Mercury is released if the lamp breaks. Special safety precautions must be taken. Information on safety and handling is available on request or can be found in the leaflet included with the lamp or in the operating instructions.



Product line drawing assembling

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321285256	SHARXS HTI 1200 W/D7/60	Shipping carton box 1	245 mm x 59 mm x 100 mm	1.45 dm <sup>3</sup>	124.00 g
4008321285263	SHARXS HTI 1200 W/D7/60	Shipping carton box 10	260 mm x 262 mm x 190 mm	12.94 dm <sup>3</sup>	1197.80 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.