



T-48 Series

Single tube (48 x 3 mm) with welded connectors offer a range of possibilities out of the ordinary. As extension, drop arm, drape weight; the possibilities are endless. The tubes use the same CCS6 connection as the trusses. Some tubes are fitted with a clamp – offering extra options for use. Single tubes are not rated with any loading capacity.



T-48-OE...OE

Non Spigoted



T-48-CC...CC

With 2 x CCS6



T-48-ST...ST

With Stabilized Coupler

Technical Specifications - T-48 Series

Type	Tube
Alloy	EN AW 6082 T6
Main Chords	48 x 3 mm
Diagonal Members	16 x 2 mm
Coupling System	CCS6

Structural data can be found at www.prolyte.com

T-48 Series - Standard available Lengths and Codes

Metres	Feet	Code	Code	Code
0.25/1.00 m in 5 mm steps	0.82'/3.28', in 0.2' steps			
0,50	1.64	T-48-OE050OE	T-48-CC050CC	T-48-ST050ST
1,00	3.28	T-48-OE100OE	T-48-CC100CC	T-48-ST100ST
1,50	4.92	T-48-OE150OE	T-48-CC150CC	T-48-ST150ST
2,00	6.56	T-48-OE200OE	T-48-CC200CC	T-48-ST200ST
2,50	8.20	T-48-OE250OE	T-48-CC250CC	\
3,00	9.84	T-48-OE300OE	T-48-CC300CC	\
4,00	13.12	T-48-OE400OE	T-48-CC450CC	\