

Type 3.1 iht NS-EN 10204:2005

Beskrivelse: Aluminiumsrør, sortlakkert, 48mm x 4mm, 6082-T6, RAL9005 Matt**Legering/herding:** EN AW 6082-T6**Farge:** Sort**Norm/Spesifikasjon:** EN 6892-1:2019**Sammensetning:**
NS-EN 573-3:2019

Comp.	Si	Fe	Cu	Mn	Mg	Cr	Zn	Ti	Al
	0,99	0,21	0,03	0,48	0,65	0,01	0,01	0,01	97,57
Min	0,70	0,00	0,00	0,40	0,60	0,00	0,00	0,00	Balanced
Max	1,30	0,50	0,10	1,00	1,20	0,25	0,20	0,10	Balanced

Holdfasthet:
NS-EN 755:2016

Nr.	Rp 0.2 N/mm ²	Rm N/mm ²	A5%	A50%	HBW (typ)
F11	345,0	365,0		10,0	
F12	340,0	363,0		11,0	
S33	331,0	345,0		10,0	
S34	328,0	346,0		9,0	
F47	343,0	364,0		11,0	
F48	343,0	366,0		11,0	
Norm.	250	290		6	
Lim.	999,0	999,0		999,0	

Prostage AS, org.nr 993062952 bekrefter med dette at overnevnte produkter er produsert iht følgende standard(er) og/eller tekniske spesifikasjon(er):

Produsert iht: EN 755-2, EN 753-3

Prostage AS
Org.nr 993062952
Tvetenveien 30
0666 Oslo
www.prostage.no
post@prostage.no

Oslo, 29/7-2024



Gunnar W. Naas
Daglig leder