

1:Specifications:		2:pictures		
Items	Parameter			
Item	128174-SBL			
Power	10W/M			
Input Voltage	AC230V	the second		
LED Source	5050SMD LEDs			
_ED quantity	80LEDs /meter			
Roll of length	100meter			
Size	W16*H8mm			
Details	every 1M cuttable	and		
P Rate	IP65			
Beam Angle	120°	\sim		
Working Environment	Working temperature:-40°C~+55°C			
	Working humidity:10%-90%			
Led Life	>50,000 hours	1		
Warranty	2 years			
Certificates	CE/RoHS	7		

3:5BL NEOTIEX 23UV RGB STrip light wavelength(hm/K)

Red	Green	Blue	Yellow	Warm white	Nature white	Cool white
619-635	512-528	463-475	584-595	2700-3300	4000-4500	5500-6500

4:Working Mode of SBL Neoflex 230V RGB

1:Can meet any customized modes! For example:

A. Running mode

Green Running, Blue Running, Red Running, Cyan Running, White Running, Purple Running, Yellow Running

B.Static mode

Static Green, Static Blue, Static Red, Static Cyan, Static White, Static purple, Static Yellow

C.Gradual change mode

Green Gradual Changing, Blue Gradual Changing, Red Gradual Changing, Cyan Gradual Changing, White Gradual Changing,

Purple Gradual Changing , Yellow Gradual Changing.

5:installing:



6:Application:

Architectural decorative lighting, Window display lighting, Amusement park or theater, Emergency lighting, Stairway accent lighting, Ad signs, light boxes, Back lighting for signage letters, Swimming pools and fountains, Swimming pools and fountains, Holiday decorative lighting, Car decorative lighting, Night club lighting

