



# A150.8 / A150.16

## Class-D Amplifiers



### Features

- A150.8 : 150 W x 8 /4Ω
- A150.16 : 150 W x 16 /4Ω
- Class-D
- Euroblock terminals

A150.8 and A150.16 are unique multi-channel amplifiers in such a compact and light format. Featuring respectively 8 and 16 channels, both models includes individual channel volume and Led signal control.

Both models are the perfect amplifiers to feed multi-zone low impedance speakers saving space in racks and giving a global visual control of the signal paths.

### Specifications

MODEL	A150.8	A150.16
<b>Power</b> (RMS, all channels driven)	130W x 8 / 4Ω 70W x 8 / 8Ω	130W x 8 / 4Ω 70W x 8 / 8Ω
<b>Input Sensitivity</b> (Limiter Off)	0.9 - 1.1V (+0/-1dBv)	
<b>Input Impedance</b>	20kΩ balanced or 10kΩ unbalanced	
<b>Frequency Response</b> (4Ω)	100Hz~15kHz (+0/-1dB)	
<b>Voltage Gain</b>	28 (+/-0.5dB)	
<b>THD + N</b> (Ref. 1kHz 1/8 Rated Power, A-Weighted)	<0.1%	
<b>S/N Ratio</b> (Ref. 1kHz, A-Weighted)	> 95dB	
<b>Crosstalk</b> (Below Rated Power)	> 70dB	
<b>Damping Factor</b> (1kHz, 8Ω)	> 200	
<b>Power/Output Circuitry</b>	Switching Power Class-D	
<b>Protections</b>	Full short circuit, open circuit, thermal, ultrasonic, and RF protection stable into reactive or mismatched loads, turn ON/OFF, muting, tripped crowbar	
<b>Controls</b>	Front: On/Off Power Switch Rear: Volume Channel 1 to 8	Front: On/Off Power Switch Rear: Volume Channel 1 to 16
<b>Indicators</b>	SIGNAL: 8 green LED - CLIP 8 red LED POWER: 1 green LED - PROTECTION: 8 red LED	SIGNAL: 16 green LED - CLIP 16 red LED POWER: 1 green LED - PROTECTION: 16 red LED
<b>Connectors</b>	Inputs: Euro Block - Outputs: Euro Block	
<b>Power Supply</b>	AC: 110-120V or 220-240V 50/60Hz	
<b>Dimension</b> (W x D x H)	483 x 360 x 44 mm	
<b>Weight</b>	6.3 kg	6.8 kg

*Specifications subject to modification without notice*



**SEIKAKU TECHNICAL GROUP LIMITED**

NO.1 LANE 17, SEC.2, HAN SHI WEST ROAD, TAICHUNG 40151 TAIWAN

Tel: +886-4-22313737 Fax: +886-4-22346757 www.seikaku.hk