

Microphone Cable SC-Source MKII; 2 x 0,25 mm²; PVC Ø 6,50 mm; red

Art. No.: 200-0103

ANALOG

OFC



General Data

Article number :	200-0103
Name :	SC-Source MKII
EAN :	4049371004190
Properties :	Analog
Properties :	OFC oxygen free copper
Application area :	Stage / live
Application area :	Mobile outdoor / indoor
Application area :	Studio / Broadcast
Application area :	Installation
Application area :	ELA 100 V
Application :	Microphone Cable
Colour :	red
Colour detailed :	red
BPVo-Euroclass :	Fca

Technical Data

Signal transmission :	symmetrical
Construction :	(2LI2Y0,25mm ²)(ST)DY
Jacket material :	PVC
Jacket Ø [mm] :	6,50
Number of Channels (audio) :	1
Inner conductor (audio) :	2
Inner conductor (audio) [mm ²] :	0,25
Inner conductor Ø (audio) [mm] :	0,56
AWG (audio) :	23
Shielding :	copper spiral sleeve tin-plated 95 % + AL-fleece
Shielding factor [%] :	100
Copper strands (audio) :	128
Copper strand Ø (audio) [mm] :	0,05
Conductor insulation material :	PE
Conductor insulation Ø [mm] :	1,55
Weight per 1 m [g] :	48
Fire load per m [kWh] :	0,21
Style variant :	round
Packing :	100 m spool
Packing :	500 m spool
Temperature min. [°C] :	-25
Temperature max. [°C] :	70
Width [mm] :	6,5
Height [mm] :	6,5

Capac. cond./cond. per 1 m (audio) [pF] :	60
---	----

Capac. cond./shield. per 1 m (audio) [pF] :	110
---	-----

Insulation resist. per 1 km [GΩ] :	0,2
------------------------------------	-----

Insulation resist. per 1 km (audio) [GΩ] :	0,2
--	-----

Conductor resistance per 1 km [Ω] :	78
-------------------------------------	----

Shield. resistance per 1 km [Ω] :	25
-----------------------------------	----

Electrical Data