


Microphone Cable SC-Square 4-Core MKII; 4 x 0,20 mm²; PVC Ø 6,50 mm; black

Art. No.: 200-0301

ANALOG

OFC



General Data

| | |
|--------------------|-------------------------|
| Article number : | 200-0301 |
| Name : | SC-Square 4-Core MKII |
| EAN : | 4049371001991 |
| Properties : | Analog |
| Properties : | OFC oxygen free copper |
| Application area : | Stage / live |
| Application area : | Mobile outdoor / indoor |
| Application area : | Installation |
| Application : | Microphone Cable |
| Colour : | black |
| Colour detailed : | black |
| BPVo-Euroclass : | Fca |

Technical Data

| | |
|----------------------------------------------|-------------------------------------------------------------|
| Signal transmission : | symmetrical |
| Construction : | (4LI2Y0,20mm ²)(ST)DY |
| Jacket material : | PVC |
| Jacket Ø [mm] : | 6,50 |
| Number of Channels (audio) : | 1 |
| Inner conductor (audio) : | 4 |
| Inner conductor (audio) [mm ²] : | 0,20 |
| Inner conductor Ø (audio) [mm] : | 0,50 |
| AWG (audio) : | 24 |
| Shielding : | Copper spiral shielding tin-plated + conductive fleece-foil |
| Shielding factor [%] : | 100 |
| Copper strands (audio) : | 102 |
| Copper strand Ø (audio) [mm] : | 0,05 |
| Conductor insulation material : | PE |
| Weight per 1 m [g] : | 53 |
| UV-resistant : | yes |
| Fire load per m [kWh] : | 0,22 |
| Style variant : | round |
| Packing : | 100 m spool |
| Packing : | 500 m spool |
| Temperature min. [°C] : | -25 |
| Temperature max. [°C] : | 70 |
| Width [mm] : | 6,5 |
| Height [mm] : | 6,5 |

Electrical Data

| | |
|---------------------------------------------|-----|
| Capac. cond./cond. per 1 m (audio) [pF] : | 65 |
| Capac. cond./shield. per 1 m (audio) [pF] : | 120 |

| | |
|--------------------------------------------|-----|
| Impedance [Ω] : | 95 |
| Insulation resist. per 1 km [GΩ] : | 0,2 |
| Insulation resist. per 1 km (audio) [GΩ] : | 0,2 |
| Conductor resistance per 1 km [Ω] : | 98 |
| Shield. resistance per 1 km [Ω] : | 20 |