


Patch & Microphone Cable SC-Peacock MKII; DMX: 2 x 0,22 mm²; S-PVC; 9,2 x 4,5 mm; black

Art. No.: **200-0551**

ANALOG **DIGITAL** **OFC**



General Data

Article number :	200-0551
Name :	SC-Peacock MKII
EAN :	4049371000512
Properties :	Analog
Properties :	OFC oxygen free copper
Properties :	Digital 110 Ω AES / EBU
Application area :	Stage / live
Application area :	Studio / Broadcast
Application area :	Installation
Application :	Patch & Microphone Cable
Colour :	black
Colour detailed :	black
BPVo-Euroclass :	Fca

Technical Data

Signal transmission :	symmetrical
Construction :	[2(2LI2Y0,22mm ²)DY]Y
Jacket material :	S-PVC
Number of Channels (AES/EBU, DMX) :	2
Inner conductor (AES/EBU, DMX) :	2
Inner conductor (AES/EBU, DMX) [mm ²] :	0,22
Inner conductor Ø (AES/EBU, DMX) [mm] :	0,53
AWG (AES/EBU, DMX) :	24
Shielding :	Copper spiral sleeve
Shielding factor [%] :	95
Copper strands (AES/EBU, DMX) :	28
Copper strand Ø (AES/EBU, DMX) [mm] :	0,10
Conductor insulation material :	Foam / Skin-PE
Conductor insulation Ø [mm] :	1,30
Weight per 1 m [g] :	53,6
UV-resistant :	yes
Fire load per m [kWh] :	0,18
Style variant :	twin
Packing :	100 m spool
Temperature min. [°C] :	-30
Temperature max. [°C] :	70
Width [mm] :	9,2
Height [mm] :	4,5

Electrical Data

Capac. cond./cond. per 1 m (AES/EBU, DMX) [pF] :	70
Capac. cond./shield. per 1 m (AES/EBU, DMX) [pF] :	125

Impedance [Ω] :	110
Insulation resist. per 1 km [GΩ] :	0,5
Insulation resist. per 1 km (AES/EBU, DMX) [GΩ] :	0,5
Conductor resistance per 1 km [Ω] :	90
Shield. resistance per 1 km [Ω] :	36