


## Patch & Microphone Cable SC-Peacock MKII; DMX: 2 x 0,22 mm<sup>2</sup>; S-PVC; 9,2 x 4,5 mm; blue Art. No.: 200-0552

ANALOG

DIGITAL

OFC



### General Data

|                    |                          |
|--------------------|--------------------------|
| Article number :   | 200-0552                 |
| Name :             | SC-Peacock MKII          |
| EAN :              | 4049371002073            |
| Properties :       | Analog                   |
| Properties :       | OFC oxygen free copper   |
| Properties :       | Digital 110 Ω AES / EBU  |
| Application area : | Stage / live             |
| Application area : | Studio / Broadcast       |
| Application area : | Installation             |
| Application :      | Patch & Microphone Cable |
| Colour :           | blue                     |
| Colour detailed :  | blue                     |
| BPVo-Euroclass :   | Fca                      |

### Technical Data

|   |                                   |
|---|-----------------------------------|
| Signal transmission :                               | symmetrical                       |
| Construction :                                      | [2(2LI2Y0,22mm <sup>2</sup> )DY]Y |
| Jacket material :                                   | S-PVC                             |
| Number of Channels (AES/EBU, DMX) :                 | 2                                 |
| Inner conductor (AES/EBU, DMX) :                    | 2                                 |
| Inner conductor (AES/EBU, DMX) [mm <sup>2</sup> ] : | 0,22                              |
| Inner conductor Ø (AES/EBU, DMX) [mm] :             | 0,53                              |
| AWG (AES/EBU, DMX) :                                | 24                                |
| Shielding :   | Copper spiral sleeve              |
| Shielding factor [%] :                              | 95                                |
| Copper strands (AES/EBU, DMX) :                     | 28                                |
| Copper strand Ø (AES/EBU, DMX) [mm] :               | 0,10                              |
| Conductor insulation material :                     | Foam / Skin-PE                    |
| Conductor insulation Ø [mm] :                       | 1,30                              |
| Weight per 1 m [g] :                                | 53,6                              |
| Fire load per m [kWh] :                             | 0,18                              |
| Style variant :                                     | twin                              |
| Packing :   | 100 m spool                       |
| Temperature min. [°C] :                             | -30                               |
| Temperature max. [°C] :                             | 70                                |
| Width [mm] :  | 9,2                               |
| Height [mm] :                                       | 4,5                               |

### Electrical Data

|  |     |
|--|-----|
| Capac. cond./cond. per 1 m (AES/EBU, DMX) [pF] :   | 70  |
| Capac. cond./shield. per 1 m (AES/EBU, DMX) [pF] : | 125 |
| Impedance [Ω] :                                    | 110 |

|   |     |
|---|-----|
| Insulation resist. per 1 km [GΩ] :                | 0,5 |
| Insulation resist. per 1 km (AES/EBU, DMX) [GΩ] : | 0,5 |
| Conductor resistance per 1 km [Ω] :               | 90  |
| Shield. resistance per 1 km [Ω] :                 | 36  |