

## Microphone Cable SC-CLUB BLACK ZILK; 2 x 0,25 mm<sup>2</sup>; S-PVC Ø 7,30 mm; black

Art. No.: 200-0711

ANALOG

DIGITAL

OFC



### General Data

Article number :	200-0711
Name :	SC-CLUB BLACK ZILK
EAN :	4049371237178
Properties :	Analog
Properties :	OFC oxygen free copper
Properties :	Digital 110 Ω AES / EBU
Application area :	Mobile outdoor / indoor
Application area :	Studio / Broadcast
Application area :	Installation
Application :	Microphone Cable
Colour :	black
Colour detailed :	black
BPVo-Euroclass :	Fca

Capac. cond./shield. per 1 m (audio) [pF] :	100
---	-----

Impedance [Ω] :	110
-----------------	-----

Insulation resist. per 1 km [GΩ] :	0,2
------------------------------------	-----

Conductor resistance per 1 km [Ω] :	78
-------------------------------------	----

Shield. resistance per 1 km [Ω] :	10
-----------------------------------	----

### Technical Data

Signal transmission :	symmetrical
Construction :	(2LI2Y0,25mm <sup>2</sup> )(ST)CY
Jacket material :	S-PVC
Jacket Ø [mm] :	7,30
Number of Channels (audio) :	1
Inner conductor (audio) :	2
Inner conductor (audio) [mm <sup>2</sup> ] :	0,25
AWG (audio) :	23
Shielding :	Copper spiral shielding 95 % + carbon semiconductor
Shielding factor [%] :	100
Copper strands (audio) :	65
Copper strand Ø (audio) [mm] :	0,07
Conductor insulation material :	HD-PP Gas-injected
Conductor insulation Ø [mm] :	1,55
Weight per 1 m [g] :	57,6
UV-resistant :	yes
Fire load per m [kWh] :	0,2
Style variant :	round
Packing :	100 m spool
Packing :	bulk stock
Temperature min. [°C] :	-25
Temperature max. [°C] :	70
Width [mm] :	7,3
Height [mm] :	7,3

### Electrical Data

Capac. cond./cond. per 1 m (audio) [pF] :	50
---	----