


**control lead SC-Control Flex; 10 x0,34 mm²;
PVC, flame-retardant, Ø 7,70 mm; grey; Eca
Art. No.: 380-0056-10034**

ANALOG

OFC



General Data

Article number :	380-0056-10034
Name :	SC-Control Flex
EAN :	4049371005067
Properties :	Analog
Properties :	OFC oxygen free copper
Application area :	Mobile outdoor / indoor
Application area :	Studio / Broadcast
Application area :	Installation
Application area :	ELA 100 V
Application :	control lead
Colour :	grey
Colour detailed :	grey
BPVo-Euroclass :	

Technical Data

Construction :	LIY-CY
Jacket material :	PVC, flame-retardant
Jacket material (control) :	PVC, flame-retardant and self-extinguishing accord.
Jacket Ø [mm] :	7,70
Number of Channels (control) :	10
Inner conductors (control) [mm ²] :	0,34
Inner conductor Ø (control) [mm] :	0,66
AWG (control) :	22
Shielding :	Copper braiding tin-plated
Shielding factor [%] :	90
Copper strands (control) :	7
Copper strand Ø (control) [mm] :	0,25
Conductor insulation material :	PVC, flame-retardant and self-extinguishing accord.
Weight per 1 m [g] :	110
Style variant :	round
Packing :	100 m spool
Packing :	500 m spool
Temperature min. [°C] :	-30
Temperature max. [°C] :	80
Width [mm] :	7,7
Height [mm] :	7,7

Electrical Data

Capacity wire/wire at 1m (control) [pF] :	120
Capacity wire/electic screen at 1m (control) [pF] :	240
Insulation resist. per 1 km [GΩ] :	0,2

Insulation resist. per 1 km (control) [GΩ] :	0,2
Conductor resistance per 1 km [Ω] :	138