


Power Lead NYM-O; 2 x 1,50 mm²; PVC, flame-retardant, Ø 8,00 mm; grey

Art. No.: 720-0036-02015

ANALOG

OFC



General Data

Article number :	720-0036-02015
Name :	NYM-O
EAN :	4049371051750
Properties :	Analog
Properties :	OFC oxygen free copper
Application area :	Installation
Application area :	ELA 100 V
Application :	Power Lead
Colour :	grey
Colour detailed :	grey
Old article number :	720-0031-02015
BPVo-Euroclass :	Fca

Technical Data

Construction :	NYM-J
Jacket material :	PVC, flame-retardant
Jacket material (power) :	PVC, flame retardant and self-extinguishing
Jacket Ø [mm] :	8,00
Number of Channels (power) :	1
Inner conductor (power) :	2
Inner conductor (power) [mm ²] :	1,50
Inner conductor Ø (power) [mm] :	1,38
AWG (power) :	15
Copper strands (power) :	1
Copper strand Ø (power) [mm] :	1,38
Conductor insulation material :	PVC
Weight per 1 m [g] :	104,4
Style variant :	round
Packing :	bulk stock
Temperature min. [°C] :	-40
Temperature max. [°C] :	70
Width [mm] :	8
Height [mm] :	8

Electrical Data

Insulation resist. per 1 km [GΩ] :	0,02
Insulation resist. per 1km (power) [GΩ] :	0,02
Test voltage [V] :	2000
Nominal voltage (power) [V] :	500
Operating voltage (power) [V] :	350