

# Speaker Cable Meridian Mobile SP215; 2 x 1,50 mm<sup>2</sup>; PVC Ø 6,80 mm; white, without imprint

Art. No.: **415-0050NE**

ANALOG

OFC



## General Data

|                    |                         |
|--------------------|-------------------------|
| Article number :   | 415-0050NE              |
| Name :             | Meridian Mobile SP215   |
| EAN :              | 4049371217804           |
| Properties :       | Analog                  |
| Properties :       | OFC oxygen free copper  |
| Application area : | Stage / live            |
| Application area : | Mobile outdoor / indoor |
| Application area : | Studio / Broadcast      |
| Application area : | ELA 100 V               |
| Application :      | Speaker Cable           |
| Colour :           | white                   |
| Colour detailed :  | white, without imprint  |
| BPVo-Euroclass :   | Fca                     |

## Technical Data

|  |                             |
|--|-----------------------------|
| Construction :                               | (2LIY1,50mm <sup>2</sup> )Y |
| Jacket material :                            | PVC                         |
| Jacket Ø [mm] :                              | 6,80                        |
| Number of Channels (audio) :                 | 1                           |
| Inner conductor (audio) :                    | 2                           |
| Inner conductor (audio) [mm <sup>2</sup> ] : | 1,50                        |
| Inner conductor Ø (audio) [mm] :             | 1,38                        |
| AWG (audio) :                                | 16                          |
| Copper strands (audio) :                     | 84                          |
| Copper strand Ø (audio) [mm] :               | 0,15                        |
| Conductor insulation Ø [mm] :                | 2,62                        |
| Weight per 1 m [g] :                         | 78                          |
| UV-resistant :                               | yes                         |
| Fire load per m [kWh] :                      | 0,28                        |
| Style variant :                              | round                       |
| Packing :                                    | 500 m spool                 |
| Packing :                                    | 100 m spool                 |
| Temperature min. [°C] :                      | -30                         |
| Temperature max. [°C] :                      | 70                          |
| Width [mm] :                                 | 6,8                         |
| Height [mm] :                                | 6,8                         |

## Electrical Data

|  |       |
|--|-------|
| Capac. cond./cond. per 1 m (audio) [pF] :  | 150   |
| Insulation resist. per 1 km [GΩ] :         | 0,005 |
| Insulation resist. per 1 km (audio) [GΩ] : | 0,005 |
| Conductor resistance per 1 km [Ω] :        | 13    |