

Speaker Cable Meridian Install SP215; 2 x 1,50 mm²; FRNC, Silikon Ø 9,00 mm; orange

Art. No.: 415-0055E30

ANALOG
E30
FRNC
HALOGEN-FREE
OFC



General Data

Article number :	415-0055E30
Name :	Meridian Install SP215
EAN :	4049371083652
Properties :	Analog
Properties :	Halogen-free / LSZH
Properties :	FRNC flame retardant
Properties :	OFC oxygen free copper
Properties :	Protection class E30
Application area :	Studio / Broadcast
Application area :	Installation
Application area :	ELA 100 V
Application :	Speaker Cable
Application :	Installation cable
Colour :	orange
Colour detailed :	orange
BPVo-Euroclass :	Fca

Insulation resist. per 1 km [GΩ] :	0,005
------------------------------------	-------

Insulation resist. per 1 km (audio) [GΩ] :	0,005
--	-------

Conductor resistance per 1 km [Ω] :	13
-------------------------------------	----

Technical Data

Construction :	(2LIH1,50mm ²)H
Construction (audio) :	(2LIY1,50mm ²)Y
Jacket material :	FRNC, Silikon
Jacket Ø [mm] :	9,00
Number of Channels (audio) :	1
Inner conductor (audio) :	2
Inner conductor (audio) [mm ²] :	1,50
Inner conductor Ø (audio) [mm] :	1,38
AWG (audio) :	16
Copper strands (audio) :	30
Copper strand Ø (audio) [mm] :	0,25
Conductor insulation Ø [mm] :	2,80
Weight per 1 m [g] :	120
Fire load per m [kWh] :	0,29
Style variant :	round
Packing :	100 m spool
Packing :	500 m spool
Temperature min. [°C] :	-30
Temperature max. [°C] :	90
Width [mm] :	9
Height [mm] :	9

Electrical Data

Capac. cond./cond. per 1 m (audio) [pF] :	150
Surge impedance (audio) [Ω] :	0