

Installation cable Meridian Install SP225; 2 x 2,50 mm²; FRNC, Silicon, E30 Ø 11,90 mm; orange

Art. No.: 425-0055E30M

ANALOG **E30** **FRNC** **HALOGEN-FREE** **OFC**



General Data

Article number :	425-0055E30M
Name :	Meridian Install SP225
EAN :	4049371413589
Properties :	Protection class E30
Properties :	OFC oxygen free copper
Properties :	FRNC flame retardant
Properties :	Halogen-free / LSZH
Properties :	Analog
Application area :	ELA 100 V
Application area :	Installation
Application area :	Studio / Broadcast
Application :	Installation cable
Application :	Speaker Cable
Colour :	orange
Colour detailed :	orange
BPVo-Euroclass :	Fca

Technical Data

Construction :	(2LIY2,5mm ²)Y
Jacket material :	FRNC, Silicon, E30
Jacket Ø [mm] :	11,90
Number of Channels (audio) :	1
Inner conductor (audio) :	2
Inner conductor (audio) [mm ²] :	2,50
AWG (audio) :	13
Copper strands (audio) :	1
Conductor insulation Ø [mm] :	3,30
Weight per 1 m [g] :	151
UV-resistant :	yes
Fire load per m [kWh] :	0,38
Style variant :	round
Packing :	500 m spool
Packing :	100 m spool
Temperature min. [°C] :	-40
Temperature max. [°C] :	90
Width [mm] :	11,9
Height [mm] :	11,9

Electrical Data

Capac. cond./cond. per 1 m (audio) [pF] :	136
Insulation resist. per 1 km [GΩ] :	0,005
Insulation resist. per 1 km (audio) [GΩ] :	0,005
Conductor resistance per 1 km [Ω] :	7,5