

## Speaker Cable Meridian Install SP225; 2 x 4,00 mm<sup>2</sup>; FRNC, Silicon, E30 Ø 12,80 mm; orange Art. No.: 440-0055E30M

ANALOG
E30
FRNC
HALOGEN-FREE
OFC



### General Data

Name :	Meridian Install SP225
EAN :	4049371372756
Properties :	Analog
Properties :	Halogen-free / LSZH
Properties :	FRNC flame retardant
Properties :	OFC oxygen free copper
Properties :	Protection class E30
Application area :	Studio / Broadcast
Application area :	Installation
Application area :	ELA 100 V
Application :	Speaker Cable
Application :	Installation cable
Colour :	orange
Colour detailed :	orange
BPVo-Euroclass :	Fca

### Technical Data

Construction :	(2LIY4,0mm <sup>2</sup> )Y
Jacket material :	FRNC, Silicon, E30
Jacket Ø [mm] :	12,80
Number of Channels (audio) :	1
Inner conductor (audio) :	2
Inner conductor (audio) [mm <sup>2</sup> ] :	4,00
AWG (audio) :	11
Copper strands (audio) :	1
Conductor insulation Ø [mm] :	3,90
Weight per 1 m [g] :	260
UV-resistant :	yes
Fire load per m [kWh] :	0,54
Style variant :	round
Packing :	100 m spool
Packing :	500 m spool
Temperature min. [°C] :	-40
Temperature max. [°C] :	90
Width [mm] :	12,8
Height [mm] :	12,8

### Electrical Data

Capac. cond./cond. per 1 m (audio) [pF] :	125
Insulation resist. per 1 km [GΩ] :	0,005
Insulation resist. per 1 km (audio) [GΩ] :	0,005
Conductor resistance per 1 km [Ω] :	4,5