

**Installation cable Meridian Install SP225 CPR-
Version; 2 x 2,50 mm²; FRNC Ø 8,20 mm;
black; Cca**
Art. No.: **425-0051FC**

ANALOG **FRNC** **HALOGEN-FREE** **OFC**

**General Data**

| | |
|--------------------|--|
| Name : | Meridian Install SP225 CPR- Version |
| EAN : | 4049371375320 |
| Properties : | OFC oxygen free copper |
| Properties : | FRNC flame retardant |
| Properties : | Halogen-free / LSZH |
| Properties : | Analog |
| Application area : | ELA 100 V |
| Application area : | Installation |
| Application area : | Studio / Broadcast |
| Application : | Installation cable |
| Application : | Speaker Cable |
| Colour : | black |
| Colour detailed : | black |
| BPVo-Euroclass : | Cca |

Technical Data

| | |
|--|----------------------------|
| Construction : | (2LIY2,5mm ²)Y |
| Jacket material : | FRNC |
| Jacket Ø [mm] : | 8,20 |
| Number of Channels (audio) : | 1 |
| Inner conductor (audio) : | 2 |
| Inner conductor (audio) [mm ²] : | 2,50 |
| Inner conductor Ø (audio) [mm] : | 1,78 |
| AWG (audio) : | 13 |
| Copper strands (audio) : | 50 |
| Copper strand Ø (audio) [mm] : | 0,25 |
| Conductor insulation Ø [mm] : | 3,05 |
| UV-resistant : | yes |
| Fire load per m [kWh] : | 0,38 |
| Style variant : | round |
| Packing : | 500 m spool |
| Packing : | 100 m spool |
| Temperature min. [°C] : | -30 |
| Temperature max. [°C] : | 70 |
| Width [mm] : | 8,2 |
| Height [mm] : | 8,2 |

Electrical Data

| | |
|--|-------|
| Capac. cond./cond. per 1 m (audio) [pF] : | 136 |
| Insulation resist. per 1 km [GΩ] : | 0,005 |
| Insulation resist. per 1 km (audio) [GΩ] : | 0,005 |
| Conductor resistance per 1 km [Ω] : | 7,5 |