

Speaker Cable Elephant Robust SPM440; 4 x 4,00 mm²; PUR Ø 11,00 mm; black

Art. No.: 490-0251-440

ANALOG
AQUA
HALOGEN-FREE
OFC
PUR



General Data

Article number :	490-0251-440
Name :	Elephant Robust SPM440
EAN :	4049371002226
Properties :	Analog
Properties :	Halogen-free / LSZH
Properties :	PUR
Properties :	OFC oxygen free copper
Properties :	Underwater / submerged
Application area :	Stage / live
Application area :	Mobile outdoor / indoor
Application area :	Studio / Broadcast
Application area :	Installation
Application area :	ELA 100 V
Application :	Speaker Cable
Colour :	black
Colour detailed :	black
BPVo-Euroclass :	Fca

Conductor resistance per 1 km [Ω] :	4,5
Test voltage [V] :	2000

Technical Data

Construction :	(4LIY4,0mm ²)Y
Jacket material :	PUR
Jacket Ø [mm] :	11,00
Number of Channels (audio) :	1
Inner conductor (audio) :	4
Inner conductor (audio) [mm ²] :	4,00
Inner conductor Ø (audio) [mm] :	2,26
AWG (audio) :	11
Copper strands (audio) :	224
Copper strand Ø (audio) [mm] :	0,15
Conductor insulation Ø [mm] :	3,75
Weight per 1 m [g] :	246
UV-resistant :	yes
Fire load per m [kWh] :	0,85
Style variant :	round
Packing :	bulk stock
Temperature min. [°C] :	-30
Temperature max. [°C] :	70
Width [mm] :	11
Height [mm] :	11

Electrical Data

Insulation resist. per 1 km [GΩ] :	0,005
Insulation resist. per 1 km (audio) [GΩ] :	0,005